

Schneider 140NOM21200C Manual

Brand	Schneider
Product Series	Schneider
Product Type	DIO head-end adaptor

Description

The Schneider Electric 140NOM21200C from the Modicon Quantum series serves as a DIO head-end adapter. It supports two Modbus RS-485 interfaces and a single Modbus RS-232 interface with a maximum transmission rate of 1 Mbps, ensuring robust communication capabilities.

- Technical specifications for 140NOM21200C
- Manufacturer Schneider Electric
 - Product Type DIO head-end adaptor
 - Product Line Modicon Quantum
 - Part Number 140NOM21200C
 - EAN 3595861136250
 - Interfaces 2 Modbus RS-485, 1 Modbus RS-232
 - Transmission Rate 1 Mbps
 - I/O Words 30 I/32 O
 - Power Dissipation 4 W
 - Standards UL 508
 - Bus Current Requirement 780 mA
 - Ambient Temperature 0 to 60 °C
 - Humidity 95 % without condensation
 - Operating Altitude <= 16404.2 ft (5000 m)
 - Protective Treatment Conformal coating
 - Resistance to Electrostatic Discharge 4 kV contact, 8 kV on air

www.AutoDCSTech.com

Description

The 140NOM21200C is a DIO head-end adapter essential for Schneider Electric's Modicon Quantum series. It is designed with versatile communication features, including two Modbus RS-485 interfaces and one Modbus RS-232 interface, capable of achieving a transmission speed of 1 Mbps.

With the capacity to handle 30 input and 32 output words, this module facilitates substantial data management within automated systems. The device operates with a power dissipation of 4 watts and complies with UL 508 standards. A bus current of 780 mA is necessary for its operation. This adaptor has a resilient operating range, capable of functioning in ambient temperatures from 0 to 60 °C. It can withstand humidity levels up to 95% without the risk of condensation forming.

In terms of environmental resilience, it can operate at altitudes reaching 16,404.2 feet (5000 meters), ensuring adaptability in various installations. The unit features a conformal coating for additional protection. Moreover, it is designed to resist electrostatic discharge, with a rating of 4 kV for contact and 8 kV for air discharge. This makes the 140NOM21200C suitable for demanding industrial applications.

- Range of product
- Modicon Quantum automation platform

Product or component type

DIO head-end adaptor

Complementary

Product compatibility

140CRA21210

140CRA21220

Number of port

1 Modbus RS232 twisted pair redundant copper

2 Modbus Plus RS485 twisted pair redundant copper

Transmission rate

1 Mbit/s

I/O words

30 I/32 O

Checks

RAM

RAM address

Processor

Checksum

Power dissipation in W

4 W

Bus current requirement

780 mA

Environment

Resistance to electrostatic discharge

4 kV contact conforming to IEC 801-2

8 kV on air conforming to IEC 801-2

Resistance to electromagnetic fields

10 V/m 80...2000 MHz conforming to IEC 801-3

Ambient air temperature for operation

0...60 °C

Ambient air temperature for storage

-40...85 °C

Relative humidity

95 % without condensation

Operating altitude

<= 5000 m

Protective treatment

Conformal coating Humiseal 1A33

Standards

UL 508

Product certifications

DNV

C-Tick

GL

RINA

FM Class 1 Division 2

RMRS

CSA

GOST

Packing Units

Unit Type of Package 1

www.AutoDCSTech.com

PCE

Number of Units in Package 1

1

Package 1 Height

5.0 cm

Package 1 Width

16.5 cm

Package 1 Length

31.5 cm

Package 1 Weight

508.0 g

Technical Specifications

Manufacturer Schneider Electric

Product Type DIO head-end adaptor

Product Line Modicon Quantum

Part Number 140NOM21200C

EAN 3595861136250

Interfaces 2 Modbus RS-485, 1 Modbus RS-232

Transmission Rate 1 Mbps

I/O Words 30 I/32 O

Power Dissipation 4 W

Standards UL 508

Bus Current Requirement 780 mA

Ambient Temperature 0 to 60 °C

Humidity 95 % without condensation

Operating Altitude $\leq$ 16404.2 ft (5000 m)

Protective Treatment Conformal coating

Resistance to Electrostatic Discharge 4 kV contact, 8 kV on air

www.AutoDCSTech.com