

Allen-Bradley 1756-ENBT Manual

Brand	Allen-Bradley
Product Series	1756
Product Type	Ethernet Communication Module

Description

Mfr. Part Number:

1756-ENBT

Manufacturer: Allen-Bradley / Rockwell Automation

Description: ControlLogix EtherNet/IP Bridge Module 10/100 Mbps, 64 TCP/IP Connections

Full Description: Allen-Bradley 1756-ENBT ControlLogix EtherNet/IP 10/100 Bridge Module - Twisted Pair, Supports a maximum of 64 TCP/IP connections and 128 Logix connections (I/O and information), 64 + 64 CIP Unconnected Messages (backplane + Ethernet); Max Number of Multicast Tags: 32; Unicast Available in RSLogix 5000 Software Version 16.03.00 or later; Socket Services; SNMP Support (password required), Duplicate IP Detection (starting in Revision 3.3); Packet Rate Capacity (packets/second): 500pps I/O, 900pps HMI/MSG The 1756-ENBT is an Allen-Bradley communication module that support Ethernet I/P communication protocol. This module has One (1) RJ45 port for connecting to Ethernet network. This Ethernet module supports 10/100 Mbps transmission speed in half or full duplex mode. Technical specifications for 1756-ENBT

Manufacturer Rockwell Automation

Brand Allen-Bradley

Part Number/Catalog No. 1756-ENBT

Module Type Ethernet Communication Module

Series ControlLogix

Current Draw (5.1 Volt DC) 700 milliamps

Ethernet-IP Communication Rate 10/100 Mbps

Current Draw (24 Volt DC) 3 milliamps

Integrated Ports One (1) RJ45; One (1) USB 1.1

Current Draw 700 mA

Insulation Voltage 30 Volts Continuous

Enclosure Open

Location Chassis (any slot)

Slot Width 1

Operating Temperature 32 to 140 degrees Fahrenheit (0 to 60 degrees Celsius)

Power Dissipation 3.7 W

Thermal Dissipation 12.6 BTU/hr

UPC 10612598269485

UNSPSC 32151705 Description

The Allen-Bradley 1756-ENBT ControlLogix Ethernet/IP Bridge Module is a copper communication module used to transfer large volumes of data using an Ethernet connection. This module can handle 64 TCP and 128 CIP connections with a communication rate of 10 / 100 Mbps. This module supports high-speed processor interlocking, control distributed I/O, and route to devices on a different NetLinx network, using the Ethernet/IP network as a backbone. These capabilities allow users to control, configure, and collect data in just one Ethernet/IP network. In turn, this allows the users to cut back on maintenance and support costs and then simplify their network architecture because fewer networks may then be required to run their application.

The 1756-ENBT is web-enabled. The module's settings and internal diagnostics such as IP traffic, TCP, UDP, collision histogram, connection management, etc. through a standard web browser. The users can also get information about the module revision, IP,

subnet, gateway, and Ethernet address, module uptime, vendor, code information, diagnostic information, name server, boot status, 1756-L1 processor mode information, and network storm information. The current draw of the 1756-ENBT module at 5.1 Volts DC is 700 milliamps. On the other hand, it has a current draw of 3 milliamps for 24 Volts DC. The power dissipation for the 1756-ENBT is at 3.7 Watts and thermal dissipation is at 12.6 BTU/hour. It can also act as a Remote I/O Adapter when placed in a remote I/O chassis. This allows the users to collect and configure data, as well as to remotely control ControlLogix modules, particularly input, output, analog, or specialty modules. Note that the 1756-ENBT does not have rotary switches. The 1756-ENBT is also backwards compatible.

The 1756-ENBT supports Ethernet I/P protocol. It is capable of connecting to 10/100 Mbps communication network with auto-negotiating function. It has a Single RJ45 communication port and a USB 1.1 configuration port.

This module is one of the earlier Ethernet modules intended for the ControlLogix automation platform. It features maximum TCP connections of 64 and 128 Common Industrial Protocol (CIP) connections. This allows simultaneous communication to different devices without the need of a multiplexer device. Up to 5000 I/O packets/sec can be and 900 HMI/MSG packets/sec can be transacted with this device. This module occupies a single slot in the chassis and may also be used in stand-alone applications. Only linear topology can be implemented with this device as it is embedded with a single Ethernet communication port.

Technical Specifications

Manufacturer Rockwell Automation

Brand Allen-Bradley

Part Number/Catalog No. 1756-ENBT

Module Type Ethernet Communication Module

Series ControlLogix

Current Draw (5.1 Volt DC) 700 milliamps

Ethernet-IP Communication Rate 10/100 Mbps

Current Draw (24 Volt DC) 3 milliamps

Integrated Ports One (1) RJ45; One (1) USB 1.1

Current Draw 700 mA

Insulation Voltage 30 Volts Continuous

Enclosure Open

Location Chassis (any slot)

Slot Width 1

Operating Temperature 32 to 140 degrees Fahrenheit (0 to 60 degrees Celsius)

Power Dissipation 3.7 W

Thermal Dissipation 12.6 BTU/hr

UPC 10612598269485

UNSPSC 32151705 Description

The Allen-Bradley 1756-ENBT ControlLogix Ethernet/IP Bridge Module is a copper communication module used to transfer large volumes of data using an Ethernet connection. This module can handle 64 TCP and 128 CIP connections with a communication rate of 10 / 100 Mbps. This module supports high-speed processor interlocking, control distributed I/O, and route to devices on a different Net