

Allen-Bradley 1762-IF4 Manual

Brand	Allen-Bradley
Product Series	1746 1747
Product Type	Analog Input Module

Description

The 1762-IF4 is a compact Four (4) Differential channels analog input module. This module supports 4-20 mA and -10 to 10V DC signals. This module is compatible for MicroLogix 1100, 1200 and 1400 Programmable Logic Controllers. Technical specifications for 1762-IF4

Manufacturer Rockwell Automation

Brand Allen-Bradley

Part Number/Catalog No. 1762-IF4

Series MicroLogix 1200

Product Type: Analog Input Module

Analog Normal Operating Voltage -10.5 to 10 Volts DC

Product Family: MicroLogix

Inputs 4 Differential (Bipolar)

Voltage signal normal ranges: '-10.5 ... +10.5V dc

Current signal normal ranges: '-21 ... +21 mA

Current signal full range: -21 ... +21 m

No. of Inputs: Four (4) Differential (Bipolar)

Mounting Type DIN Rail or Panel

Status Indicator Single source LED

Recommended Cable Belden 8761 (shielded)

Shipping Weight 8.28 ounces

UPC 10611320152125

Enclosure Type Rating IP20

Converter Delta-Sigma

Resolution: 15 bit

Repeatability: $\pm 0.12\%$

Dimensions 90 x 87 x 40.4 millimeters

Description

The 1762-IF4 is an Allen-Bradley MicroLogix 1200 with a 4-channel current/voltage analog input module. It has a Delta-Sigma converter and 4 differential (bipolar) inputs. Its analog operating voltage range is -10 to 10 Volts DC normal and -10.5 to 10.5 Volt DC full-scale. Its analog operating current range is 4 to 20 mA normal and -21 to 21 mA at full scale. This module enhanced the functionality of MicroLogix by allowing additional I/O to the system. It requires minimal spacing and can be either DIN rail or panel mounted. The module communicates and receives information on 5 to 24 Volts DC power via the 1762 bus interface. When wiring the input terminal blocks, a finger-safe cover is present. A flat ribbon cable is used to attach various I/O modules. The 1762-IF4 module supports 2-wire, 3-wire, or 4-wire transmitter configuration. During troubleshooting, users should always stand away from the equipment and always check it for any program change. Safety circuits should always be wired in series to the master relay. The 1762-IF4 module should be installed in non-hazardous, dry, and clean environments with circuits not crossing overvoltage Category II standards. To avoid damage to the module, always prevent electrostatic discharge and remove power. A field-upgradable flash operating system helps to make sure the users will always be up-to-date with the latest features without having to replace any of the hardware. The I/O count can be expanded by using rackless I/O modules. This results in larger control systems, greater application flexibility, and expandability at a lower cost and a reduced parts inventory.

This module has Four (4) input channels, each configurable for configurable to receive current and voltage signals ranging from -21 to 21 mA and -10 to +10VDC respectively.

Input signal type selection is made through the provide DIP switches. The received voltage signals passes through an Analog to Digital (ADC) converter for conversion of analog data to binary codes stored in the analog input register. The converted data may be formatted as Raw / Proportional and Scale for PID.

If used with MicroLogix 1100, up to Four (4) expansion modules are allowed which may be 1764-IF4. If installed with MicroLogix 1200, Six (6) expansion modules may be connected and Seven (7) modules may be attached to MicroLogix 1400.

Expansion modules such as the 1764-IF4 connects to the MicroLogix bus by means of the provided the ribbon cable that is connected by the pin contacts installed at the front panel of every module. This Installation of this module follows the installation method of the MicroLogix base module specifically, DIN rail or direct panel mounting installation.

The module has a dimension of 90 mm (height) x 87 mm (depth) x 40 mm (width) height including mounting tabs is 110 mm 3.54 in.

Technical Specifications

Manufacturer Rockwell Automation

Brand Allen-Bradley

Part Number/Catalog No. 1762-IF4

Series MicroLogix 1200

Product Type: Analog Input Module

Analog Normal Operating Voltage -10.5 to 10 Volts DC

Product Family: MicroLogix

Inputs 4 Differential (Bipolar)

Voltage signal normal ranges: '-10.5 ... +10.5V dc

Current signal normal ranges: 4 ... 20 mA

Current signal full range: -21 ... +21 m

No. of Inputs: Four (4) Differential (Bipolar)

Mounting Type DIN Rail or Panel

Status Indicator Single source LED

Recommended Cable Belden 8761 (shielded)

Shipping Weight 8.28 ounces

UPC 10611320152125

Enclosure Type Rating IP20

Converter Delta-Sigma

Resolution: 15 bit

Repeatability: $\pm 0.12\%$

Dimensions 90 x 87 x 40.4 millimeters Description

The 1762-IF4 is an Allen-Bradley MicroLogix 1200 with a 4-channel current/voltage analog input module. It has a Delta-Sigma converter and 4 differential (bipolar) inputs. Its analog operating voltage range is -10 to 10 Volts DC normal and -10.5 to 10.5 Volt DC full-scale.