

Schneider TSXSAZ10 Manual

Brand	Schneider
Product Series	Schneider
Product Type	AS-Interface master module

Description

The Schneider Electric TSXSAZ10 is designed as an AS-Interface master module for integration within the TSX Micro PLCs series. With a capacity to manage up to 31 server devices, it enables seamless communication and control in automation setups. It handles a total of 4 discrete inputs and 4 discrete outputs, facilitating straightforward I/O management.

Technical specifications for TSXSAZ10

Manufacturer Schneider Electric

Product Line TSX Micro PLCs

Part Number TSXSAZ10

EAN 3389110738070

Weight 1.00 lbs (0.45 kg)

Type AS-Interface master module

Compatible Cabling System AS-Interface cabling system

Addressing Option Standard

Number of Server Devices 31 devices

Discrete Input Capacity 4 inputs

Discrete Output Capacity 4 outputs

IP Rating IP20

Operating Temperature 0 to 60 degrees Celsius

Storage Temperature -25 to 70 degrees Celsius

Power Supply From host platform

Relative Humidity 5% to 95%, non-condensing

Range of Product

Modicon Premium Automation platform

Product or Component Type

AS-Interface master module

Complementary

Range Compatibility

AS-Interface cabling system

Actuator sensor interface profile [AS-i]

M2

AS-i version

V1

Addressing

Standard

Number of server device(s)

31, standard

Type of connectable interfaces

Discrete I/Os (4I/4O)

Electrical connection

Terminal block AS-Interface line

Supply

Via power supply integrated into the host platform of the module

Environment

Product Certifications

AS-Interface No 12001

Standards

IEC 60068-2-6, Fc tests

IEC 60068-2-27, Ea tests

IEC 61131-2

Ambient Air Temperature for Operation

32...140 °F (0...60 °C)

Ambient Air Temperature for Storage

-13...158 °F (-25...70 °C)

IP Degree of Protection

IP20

Ordering and shipping details

Category

US1PC1422556

Discount Schedule

PC14

GTIN

3389110738070

Returnability

No

Packing Units

Unit Type of Package 1

PCE

Nbr. of units in pkg.

1

Package 1 Height

2.2 in (5.5 cm)

Package 1 Width

2.2 in (5.7 cm)

Package 1 Length

10.04 in (25.5 cm)

Package weight(Lbs)

11.4 oz (324.0 g)

Description

The TSXSAZ10 from Schneider Electric acts as an AS-Interface master module in the TSX Micro PLCs series. It provides essential connectivity for automation systems utilizing the AS-Interface cabling framework. The module can address a maximum of 31 devices, making it effective for medium-sized setups. With 4 discrete inputs and 4 discrete outputs, it easily accommodates a range of control and signaling tasks.

Designed with an IP20 rating, this unit is best suited for environments where direct exposure to dust and moisture is limited. It functions within an operating temperature spectrum of 0 to 60 degrees Celsius, ensuring stability in various conditions. In terms of storage, it withstands lower temperatures down to -25 degrees Celsius and can tolerate up to 70 degrees Celsius. The humidity range for operational effectiveness is generous, from 5% to 95% relative humidity, provided that conditions remain non-condensing.

This module is powered from the host platform, streamlining installation and reducing the need for external power supplies, enhancing

system integration and efficiency. Overall, the TSXSAZ10 serves as a reliable component in enhancing AS-Interface setups, combining flexibility and ease of use.

Technical Specifications

Manufacturer Schneider Electric
Product Line TSX Micro PLCs
Part Number TSXSAZ10
EAN 3389110738070
Weight 1.00 lbs (0.45 kg)
Type AS-Interface master module
Compatible Cabling System AS-Interface cabling system
Addressing Option Standard
Number of Server Devices 31 devices
Discrete Input Capacity 4 inputs
Discrete Output Capacity 4 outputs
IP Rating IP20
Operating Temperature 0 to 60 degrees Celsius
Storage Temperature -25 to 70 degrees Celsius
Power Supply From host platform
Relative Humidity 5% to 95%, non-condensing
Range of Product
Modicon Premium Automation platform
Product or Component Type
AS-Interface master module
Complementary
Range Compatibility
AS-Interface cabling system
Actuator sensor interface profile [AS-i]
M2
AS-i version
V1
Addressing
Standard
Number of server device(s)
31, standard
Type of connectable interfaces
Discrete I/Os (4I/4O)
Electrical connection
Terminal block AS-Interface line
Supply
Via power supply integrated into the host platform of the module
Environ