

# ABB V18345-2020521001 Manual

Brand	ABB
Product Series	Sheet27
Product Type	Electro-Pneumatic Positioner

## Description

V18345-2020521001 | ABB | Electro-Pneumatic Positioner

Manufacturer : ABB

Product No. : V18345-2020521001

Product Type : Electro-Pneumatic Positioner

V18345-2020521001 =TZIDC Electro-Pneumatic Positioner

Case / Mounting : 2 = Case made of aluminium, varnished, protection IP 65 (NEMA 4X) for mounting to linear actuators acc. to DIN/IEC 534 / NAMUR or to rotary actuators acc. to VDI/DE 3845 as above, but with mechanical position indicator

0 : -

Input / communication port : 2 = Input 4...20 mA, two-wire FSK module for HART communication

Explosion protection : 0 = without

Output / safe position (in case of an electrical power failure) : 5 = Double acting , fail freeze

Connections : 2 = Cable: Thread 1/2-14 NPT Air pipe: Thread 1/4-18 NPT

Option modules for analog or digital position feedback : 1 = Plug-in module analog position feedback (sign. range 4 ... 20 mA)

Optional mechanical kit for digital position feedback : 0 =without

0 : -

Design (varnish / coding) : 1 = Standard

Weight : 1.7 Kg

Input

Signal

Two\_x0001\_wire technology

Nominal range 4...20 mA

Split range configuration between 20% and 100% of the nominal range

Max. 25 mA / 30 V  
Min. 3.4 mA (without analog pos. feedback)  
3.5 mA (with analog pos. feedback)  
Start from 3.8 mA  
Load voltage at 20 mA 8.7 V DC without explosion protection  
9.7 V DC for intrinsically safe device  
Impedance at 20 mA 435 ohms without explosion protection  
485 ohms for intrinsically safe device  
Digital input  
Control voltage 24 V DC (12...30 V DC)  
0...10 V DC: Logical "0"  
12...30 V DC: Logical "1"  
Current max. 4 mA  
Digital output (control circuit to DIN 19234/NAMUR)  
Supply voltage. 5...11 V DC  
Current < 1.0 mA Logical "0"  
Current > 2.0 mA Logical "1"  
Effective direction: normally logical "0" or logical "1"  
(configurable)  
Output  
Range  
0...6 bar (0...90 psi)  
Air capacity  
at supply pressure of 1.4 bar (20 psi)  
5.0 kg/h = 3.9 Nm<sup>3</sup>/h = 2.3 scfm  
at supply pressure of 6 bar (90 psi)  
13 kg/h = 10 Nm<sup>3</sup>/h = 6.0 scfm (Booster on request)  
Output function  
for single or double acting actuators,  
air is vented from actuator or actuator is blocked in case of electrical  
power failure  
Shut-off values  
end position 0 % = 0...45 %  
end position 100 % = 55...100 %  
Travel  
Angle of rotation  
Used range 25...120 ° (rotary actuators, optionally 270 °)  
25...60 ° (linear actuators)

www.AutoDCSTech.com