

ABB AO845A Manual

Brand	ABB
Product Series	ABB
Product Type	Analog Output

Description

The AO845/AO845A Analog Output Module for single or redundant applications has 8 unipolar analog output channels. The module performs self-diagnostic cyclically. Module diagnostics include:

External Channel Error is reported (only reported on active channels) if the process power supply that supply voltage to output circuitry is too low, or the output current is less than the output set value and the output set value > 1 mA (open circuit).

Internal Channel Error is reported if the output circuit can not give the right current value. In a redundant pair the module will be commanded to error state by the ModuleBus master.

Module Error is reported in case of Output Transistor Error, Short Circuit, Checksum Error, Internal Power Supply Error, Status Link Error, Watchdog or Wrong OSP behavior.

Features and benefits

8 channels of 4...20 mA

For single or redundant applications

1 group of 8 channels isolated from ground

Analog inputs are short circuit secured to ZP or +24 V

HART pass-through communication

MTUs that match this product

,

TU810V1

General info

Article number 3BSE045584R1

Type Analog Output

Signal specification 4..20 mA

Number of channels 8

HART Yes

SOE No

Redundancy Yes

High integrity No

Intrinsic safety No

Mechanics S800

Detailed data

Resolution 12 bit

Isolation Groupwise isolated from ground

Under/over range -12.5% / +15%

Output load Max 750 Ω

Error Max. 0.1%

Temperature drift Max. 50 ppm/°C

Rise Time Output filter: Disable 23 ms, Enable max 4 mA / 12.5 ms

Input filter (rise time 0-90%) 23 ms (0-90%), max 4 mA / 12.5 ms

Update cycle time 10 ms

Current limiting Short circuit proof current limited output

Maximum field cable length 600 meters (656 yards)

Rated insulation voltage 50 V

Dielectric test voltage 500 V a.c.

Power dissipation Typ. 3.5 W

Current consumption +5 V Modulebus Max. 125 mA

Current consumption +24 V external 218 mA

Diagnostics

Front LED's F(ault), R(un), W(arning), O(SP)

Status indication of supervision Module Error, Module Warning, Channel error

Environment and certification

CE mark Yes

Electrical safety EN 61010-1, UL 61010-1, EN 61010-2-201, UL 61010-2-201

Hazardous Location C1 Div2 cULus, C1 Zone2 cULus, ATEX Zone 2

Marine certification BV, DNV, LR

Temperature, Operating 0 to +55 °C (+32 to +131 °F), approvals are issued for +5 to +55 °C

Temperature, Storage -40 to +70 °C (-40 to +158 °F)

Pollution degree Degree 2, IEC 60664-1

Corrosion protection ISA-S71.04; G3

Relative humidity 5 to 95 %, non-condensing

Max ambient temperature 55 °C (131 °F), for vertical mounting in compact MTU 40 °C (104 °F)

Protection class IP20 according to IEC 60529

Mechanical operating conditions IEC/EN 61131-2

EMC EN 61000-6-4 and EN 61000-6-2

Overvoltage categories IEC/EN 60664-1, EN 50178

Equipment class Class I according to IEC 61140; (earth protected)

RoHS compliance DIRECTIVE/2011/65/EU (EN 50581:2012)

WEEE compliance DIRECTIVE/2012/19/EU

Compatibility

Use with MTU TU810, TU812, TU814, TU830, TU833, TU842, TU843 or TU852

Keying code DB

Dimensions

Width 45 mm (1.77")

Depth 102 mm (4.01"), 111 mm (4.37") including connector

Height 119 mm (4.7")

Weight 0.21 kg (0.46 lbs.)