

Schneider BMEP584040 Manual

Brand	Schneider
Product Series	BME
Product Type	Processor module

Description

standalone processor, Modicon M580, 16MB, 61 Ethernet devices, 16 remote IO racks of X80 and Quantum [TAA]
BMEP584040

Main

Range of Product

Modicon M580

Product or Component Type

Processor module

Complementary

Number of racks

8

Local I/O processor capacity (discrete)

4096 I/O

Local I/O processor capacity (analog)

1024 I/O

Number of application specific channel (local rack)

144

Application specific I/O

Counter

SSI encoder

Motion control

Accurate time stamping

HART

Serial link

Checks

Process control

Control channels

Programmable loops

Integrated connection type

1 Ethernet TCP/IP service port

2 Ethernet TCP/IP device network

USB type mini B

Number of remote I/O station

16 - 2 remote drop

Number of distributed equipment

64

Communication module processor capacity

16 AS-Interface module

4 Ethernet communication module

Communication Service

www.AutoDCSTech.com

RIO scanner
DIO scanner
Memory description
Expandable flash, 4 GB data storage
Integrated RAM, 10 kB system memory
Integrated RAM, 16 MB program
Integrated RAM, 2048 kB data
Application structure
2 auxiliary tasks
1 cyclic/periodic master task
1 periodic fast task
128 event tasks
Cybersecurity
Achilles certified
DoS prevention
IPSec
SNMP logging
Syslog protocol support
Transport layer security
Audit trail
Embedded firewall
Firmware signature
Password protection
Port hardening
Secure communication (HTTPS)
Security log
Number of instructions per ms
30 Kinst/ms 65 % Boolean + 35 % fixed arithmetic
40 Kinst/ms 100 % Boolean
Current consumption
295 mA 24 V DC
MTBF reliability
775000 H
Marking
CE
Environment
Vibration resistance
3 gn
Shock resistance
30 gn
Ambient Air Temperature for Operation
32...140 °F (0...60 °C)
Ambient Air Temperature for Storage
-40...185 °F (-40...85 °C)
Operating altitude
0...6561.68 ft (0...2000 m)
2000...5000 m with derating factor
Relative humidity
5...95 % 131 °F (55 °C) without condensation
IP Degree of Protection
IP20

www.AutoDCSTech.com

Directives

2014/35/EU - low voltage directive

2014/30/EU - electromagnetic compatibility

Product certifications

CE

UL

CSA

RCM

EAC

Merchant Navy

Standards

IEC 61131-2

IEC 61010-2-201

UL 61010-2-201

CSA C22.2 No 61010-2-201

IACS E10

EN/IEC 61000-6-5, interface type 1 and type 2

EN/IEC 61850-3, location G

Environmental characteristic

Hazardous location class I division 2

Supply

Internal power supply via rack

Status LED

1 LED (Green) processor running (RUN)

1 LED (Red) processor or system fault (ERR)

1 LED (Red) I/O module fault (I/O)

1 LED (Green) download in progress (DL)

1 LED (Red) memory card or CPU flash fault (BACKUP)

1 LED (green/red) ETH MS (Ethernet port configuration status)

1 LED (green/red) Eth NS (Ethernet network status)

Net Weight

1.872 lb(US) (0.849 kg)

Ordering and shipping details

Category

US1PC3418161

Discount Schedule

PC34

GTIN

3595864174464

Returnability

Yes

Country of origin

FR

Packing Units

Unit Type of Package 1

PCE

Nbr. of units in pkg.

1

Package 1 Height

3.46 in (8.800 cm)

Package 1 Width

www.AutoDCSTech.com

6.81 in (17.300 cm)

Package 1 Length

9.84 in (25.000 cm)

Package weight(Lbs)

30.864 oz (875.000 g)

Unit Type of Package 2

S03

Number of Units in Package 2

6

Package 2 Height

11.81 in (30.000 cm)

Package 2 Width

11.81 in (30.000 cm)

Package 2 Length

15.75 in (40.000 cm)

Package 2 Weight

12.412 lb(US) (5.630 kg)

www.AutoDCSTech.com