

Schneider TSXCAY22 Manual

Brand	Schneider
Product Series	Schneider
Product Type	Proportional with overshoot compensation and gain switching (2 ms)

Description

The Schneider Electric TSXCAY22 is a multifunctional control module designed for a range of servo applications. It facilitates precise motion control and is adaptable to different servo systems with a variety of input compatibility options.

Technical specifications for TSXCAY22

Manufacturer Schneider Electric

Product Line Modicon

Part Number TSXCAY22

EAN 3389110123678

Weight 1.00 lbs (0.45 kg)

Power Dissipation 7.2 to 11.5 W

Servo Loop Type Proportional with overshoot compensation and gain switching (2 ms)

Speed Profile Path Trapezoidal or parabolic

Axis Length 256 to 32,000,000 P

Acquisition Speed 54,000 to 270,000 points/min

Acceleration Time 8 ms to 10 seconds

Operating Modes FOLLOWER, OFF, Direct Drive Mode, Manual, Automatic

Axis Type Following axis dynamic ratio, Limited axis, Infinite axis

Clock Frequency 200 kHz (SSI absolute encoder)

Input Compatibility Incremental encoder 10-30V totem pole, Incremental encoder 5V DC RS422, Absolute encoder SSI output (12-25 bits)

Input Voltage 24V, 8mA (auxiliary input, servo drive control input)

Number of Outputs 2 Reflex static outputs, 2 Analog static outputs, 2 Servo drive validation relay outputs

Analog Output Range ± 10 to 24V with 13-bit + sign resolution

Description

The TSXCAY22 by Schneider Electric is tailored for sophisticated servo control applications. This module is engineered to handle power dissipation ranging from 7.2 to 11.5 watts, providing efficient performance under various operating conditions. The servo loop is designed with proportional control, featuring overshoot compensation and gain switching with a response time of 2 milliseconds.

Users can choose from trapezoidal or parabolic speed profile paths, ensuring versatility in motion control. The module accommodates an axis length that can range from 256 to 32 million pulses, making it suitable for both short and extensive applications. Acquisition speed is robust, allowing for data collection at a rate between 54,000 and 270,000 points per minute. Adjustments in acceleration can be made swiftly within a window of 8 milliseconds to 10 seconds.

Operating modes are diverse, including Follower, Manual, Automatic, and Direct Drive Mode, catering to various system requirements. The axis types offered are Following axis dynamic ratio, Limited axis, and Infinite axis. With a clock frequency of 200 kHz for SSI absolute encoders, the module ensures accurate data representation.

Input compatibility includes various incremental encoders operating at 10-30V and 5V DC RS422, as well as absolute encoders with

SSI outputs ranging from 12 to 25 bits, enhancing flexibility. The auxiliary input operates at 24V with an 8mA capacity for servo drive control. The number of outputs consists of 2 Reflex static outputs, 2 Analog static outputs, and 2 validation relay outputs for the servo drive.

The analog output can vary between ± 10 to 24 volts, providing a resolution of 13 bits plus sign, which is crucial for fine-tuning operations. Overall, the TSXCAY22 module excels in delivering precise control and is suited for various servo-driven applications.

Range of Product

Modicon Premium Automation platform

Product or Component Type

Motion control modules

Product Specific Application

For servo motors

Servo loop type

Proportional to overshoot compensation and gain switching 2 ms

Checks

Presence of voltage/sensor feedback counter input

Consistency of commands

Encoder coupling, servo drive present, emergency stop

Proper execution of movement

Sensor power supply

Validity of parameters

Complementary

Speed profile path

Trapezoidal or parabolic

Resolution

≥ 0.5 position units per point

≤ 1000 position units per point

Length of axis

256...32000000 P

Acquisition speed

≤ 270000 points/mn

≥ 54000 points/mn

Acceleration time

8 ms...10 s

Operating Mode

FOLLOWER

OFF

Direct drive mode

Manual

Automatic

Type of axis

Following axis dynamic ratio

Limited axis

Infinite axis

Function of module

Cut on the fly

Servo drive offset correction

I/O modularity

2 axes

Input compatibility

www.AutoDCSTech.com

Incremental encoder 10...30 V totem pole
Incremental encoder 5 V DC RS422
With 2-wire/3-wire sensor (24 DC) auxiliary input
Absolute encoder parallel output ABE7CPA11
Absolute encoder SSI output 12...25 bits
Clock frequency
200 kHz SSI absolute encoder
Incremental encoder frequency x1
500 kHz
Incremental encoder frequency x 4
1000 kHz in counting
250 kHz in input
Power dissipation in W
7.2...11.5 W
Input type
Current sink auxiliary input EN/IEC 1131 Type 2
Resistive servo drive control input EN/IEC 1131 Type 1
Resistive counter input
Input logic
Positive
Input voltage
24 V 8 mA auxiliary input
24 V 8 mA servo drive control input
5 V 18 mA counter input
Input voltage limits
 ≤ 5.5 V counter input
19...30 V auxiliary input
19...30 V servo drive control input
Voltage state 1 guaranteed
 ≥ 11 V auxiliary input
 ≥ 11 V servo drive control input
 ≥ 2.4 V counter input
Current state 1 guaranteed
 ≥ 3.5 mA servo drive control input)
 ≥ 3.7 mA counter input)
 ≥ 6 mA auxiliary input)
Voltage state 0 guaranteed
 ≤ 1.2 V counter input
 ≤ 5 V auxiliary input
 ≤ 5 V servo drive control input
Current state 0 guaranteed
 ≤ 1 mA counter input)
 ≤ 1.5 mA servo drive control input)
 ≤ 2 mA auxiliary input)
Input impedance
270 Ohm counter input
3000 Ohm auxiliary input
3000 Ohm servo drive control input
Number of outputs
2 reflex output static EN/IEC 61131
2 analogue output static

www.AutoDCSTech.com

2 servo drive validation output relay

Analogue output range

+/- 10...24 V

Analogue output resolution

13 bits + sign

LSB value

1.25 mV analogue output

Output voltage

24 V DC reflex output:

24 V DC servo drive validation output:

Output voltage limits

Reflex output 19...30 V

Servo drive validation output 5...30 V

Nominal output current

0.5 A reflex output

Maximum output current

1.5 mA analogue output

200 mA servo drive validation output

625 mA reflex output

Minimum load

1 mA 1 V

Maximum voltage drop

<1 V at state on reflex output

Maximum leakage current

0.3 mA reflex output

Switching time

< 5 ms for servo drive validation

< 500 μ s for reflex output

Output compatibility

Positive logic DC inputs (resistance $\leq$ 15 kOhm) reflex

Short-circuit protection

Current limiter reflex output

Thermal tripping reflex output

Output overload protection

Current limiter reflex output

Thermal tripping reflex output

Output overvoltage protection

Zener diode between outputs and 24 DC reflex output

Reverse polarity protection

Reflex output reverse diode on supply

Local signalling

1 LED (green) for module operating (RUN)

1 LED (red) for external fault (I/O)

1 LED (red) for internal fault, module failure (ERR)

2 LEDs (green) for axis diagnostics available

Electrical connection

1 connector HE-10 20 pins for aux inputs, reflex output, for external sensor and preactuator power supply

1 connector HE-10 20 pins for servo drive ctrl inputs + for ext power supply of servo drive inputs/outputs

1 connector SUB-D 9 for an analogue output (speed reference)

2 connectors SUB-D 15 for an incremental or absolute encoder

Current consumption

www.AutoDCSTech.com

11...20 mA 24 V DC on 10/30 V absolute encoder module

1100 mA 5 V DC

15 mA 24 V DC

Module format

Standard

Net Weight

1.06 lb(US) (0.48 kg)

Environment

Protective treatment

TC

Ambient Air Temperature for Operation

32...140 °F (0...60 °C)

Ambient Air Temperature for Storage

-13...158 °F (-25...70 °C)

Relative Humidity

5...95 % without condensation

Operating altitude

<= 6561.68 ft (2000 m)

Technical Specifications

Manufacturer Schneider Electric

Product Line Modicon

Part Number TSXCAY22

EAN 3389110123678

Weight 1.00 lbs (0.45 kg)

Power Dissipation 7.2 to 11.5 W

Servo Loop Type Proportional with overshoot compensation and gain switching (2 ms)

Speed Profile Path Trapezoidal or parabolic

Axis Length 256 to 32,000,000 P

Acquisition Speed 54,000 to 270,000 points/min

Acceleration Time 8 ms to 10 seconds

Operating Modes FOLLOWER, OFF, Direct Drive Mode, Manual, Automatic

Axis Type Following axis dynamic ratio, Limited axis, Infinite axis

Clock Frequency 200 kHz (SSI absolute encoder)

Input Compatibility Incremental encoder 10-30V totem pole, Incremental encoder 5V DC RS422, Absolute encoder SSI output (12-25 bits)

Input Voltage 24V, 8mA (auxiliary input, servo drive control input)

Number of Outputs 2 Reflex static outputs, 2 Analog static outputs, 2 Servo drive validation relay outputs

Analog Output Range ± 10 to 24V with 13-bit + sign resolution