

Schneider TSXP57203M Manual

Brand	Schneider
Product Series	Schneider
Product Type	Ethernet TCP/IP RJ45, Serial link 2 female mini DIN RS485 19.2 kbit/s

Description

The TSXP57203M from Schneider Electric is part of the TSX Micro PLC series. It features advanced processing capabilities, including a fast task overhead of 0.3 milliseconds and a master task overhead of 1 millisecond. This unit is designed for efficient program execution with a memory capacity of 224 KB when using a PCMCIA card.

Technical specifications for TSXP57203M

Manufacturer Schneider Electric

Product Line TSX Micro PLCs

Part Number TSXP57203M

EAN 3595862023849

Weight 1.00 lbs (0.45 kg)

System Overhead 0.3 ms fast task, 1 ms master task

Memory Description Internal RAM: 224 KB program and 96 KB data with PCMCIA card; 96 KB program and data without PCMCIA card

PCMCIA Card 256 KB additional data storage

Execution Time per Instruction 0.19 μ s Boolean without PCMCIA card, 0.25 μ s Boolean with PCMCIA card

Number of Instructions per ms 2.1 Kinst/ms (with PCMCIA card: 65% Boolean + 35% fixed arithmetic), 3.71 Kinst/ms (without PCMCIA card: 65% Boolean + 35% fixed arithmetic)

Current Consumption 1650 mA, 5 V DC

Module Format Standard

Communication Module Processor Capacity 2 modules

Integrated Connection Type Ethernet TCP/IP RJ45, Serial link 2 female mini DIN RS485 19.2 kbit/s

Analogue I/O Processor Capacity 24 I/O

Discrete I/O Processor Capacity 512 I/O

Number of Racks 2 (12 slots), 4 (4/6/8 slots)

Internal RAM 96 KB data

Application Structure 1 master task, 1 fast task, 32 event tasks

Description

The Schneider Electric TSXP57203M is a compact programmable logic controller designed for high-speed processing and control. It features a system overhead with a fast task execution time of 0.3 milliseconds and a master task time of 1 millisecond, facilitating quick responses in automation applications. The internal RAM allows for 224 KB of program storage and 96 KB of data while utilizing a PCMCIA card. Users can also utilize an additional 256 KB of storage with the card installed.

For instruction efficiency, this PLC achieves execution times per instruction of 0.19 microseconds for Boolean operations when not using a PCMCIA card, increasing to 0.25 microseconds when engaged. The processing capability peaks at 3.71 Kinst/ms without the PCMCIA and 2.1 Kinst/ms with it, ensuring robust performance for complex tasks.

With a standard module format, the TSXP57203M weighs approximately 0.84 lbs. (0.38 kg) and supports up to two communication modules. It is equipped with integrated connection types such as Ethernet TCP/IP via an RJ45 interface and a serial link utilizing

female mini-DIN RS485 at 19.2 kbit/s for flexible networking options. Additionally, the PLC facilitates 512 discrete I/O and 24 analog I/O points, enhancing its applicability in diverse control systems.

Its structure includes 1 master task, a fast task, and up to 32 event tasks. The TSXP57203M thus stands as a competent solution for advanced automation requirements, fulfilling the need for efficiency and adaptability in various operational frameworks.

Range of Product

Modicon Premium Automation platform

Product or Component Type

Double-format PL7 processor

Software Designation

PL7 Junior/Pro

Complementary

Number of racks

16 4/6/8 slots

8 12 slots

Number of slots

96

64

128

Discrete I/O processor capacity

1024 I/O

Analogue I/O processor capacity

80 I/O

Number of application specific channel

24

Number of process control channel

10 up to 30 simple loops

Integrated connection type

Non isolated serial link 2 female mini DIN19.2 kbit/s)

Communication module processor capacity

1 fieldbus module (none if CANopen used)

1 network module

4 AS-Interface bus modules

1 CANopen

Memory description

Internal RAM (with PCMCIA card) 48 Kwords data

Internal RAM (without PCMCIA card) 48 Kwords program and data

PCMCIA card 160 Kwords program

PCMCIA card 2688 Kwords additional data storage

Maximum size of object areas

30.5 %MWi internal words located internal data

32 %KWi constant words located internal data

8132 %Mi located internal bits

Application structure

1 fast task

1 master task

64 event tasks

Execution time per instruction

0.19 μ s Boolean without PCMCIA card

0.21 μ s Boolean with PCMCIA card

0.25 μ s word or fixed-point arithmetic without PCMCIA card
0.42 μ s word or fixed-point arithmetic with PCMCIA card
2.6 μ s floating points with PCMCIA card
2.6 μ s floating points without PCMCIA card
Number of instructions per ms
2.5 Kinst/ms 65 % Boolean + 35 % fixed arithmetic with PCMCIA card
3.57 Kinst/ms 65 % Boolean + 35 % fixed arithmetic without PCMCIA card
3.7 Kinst/ms 100 % Boolean with PCMCIA card
4.76 Kinst/ms 100 % Boolean without PCMCIA card
System overhead
0.35 ms fast task
1 ms master task
Marking
CE
Local signalling
1 LED (green) for processor running (RUN)
1 LED (red) for I/O module or configuration fault (I/O)
1 LED (red) for processor or system fault (ERR)
1 LED (yellow) for activity on the terminal port (TER)
Current consumption
750 mA 5 V DC
Module format
Double
Net Weight
1.15 lb(US) (0.52 kg)
Environment
Standards
CSA C22.2 No 142
UL 508
CSA C22.2 No 213 Class I Division 2 Group A
IEC 61131-2
89/336/EEC
73/23/EEC
CSA C22.2 No 213 Class I Division 2 Group C
92/31/EEC
CSA C22.2 No 213 Class I Division 2 Group B
93/68/EEC
CSA C22.2 No 213 Class I Division 2 Group D
Product Certifications
LR
DNV
RMRS
GL
RINA
BV
ABS
Ambient Air Temperature for Operation
32...140 °F (0...60 °C)
Ambient Air Temperature for Storage
-13...158 °F (-25...70 °C)
Relative Humidity

www.AutoDCSTech.com

10...95 % without condensation for operation

5...95 % without condensation for storage

Operating altitude

0...6561.68 ft (0...2000 m)

Protective treatment

TC

IP Degree of Protection

IP20

Pollution degree

2

Ordering and shipping details

Category

22558-TSX PREMIUM, ATRIUM & PL7 PRO

Discount Schedule

PC22

GTIN

3595862023849

Returnability

No

Country of origin

FR

Packing Units

Unit Type of Package 1

PCE

Nbr. of units in pkg.

1

Package 1 Height

3.7 in (9.5 cm)

Package 1 Width

7.09 in (18.0 cm)

Package 1 Length

10.2 in (26.0 cm)

Package weight(Lbs)

22.8 oz (646.0 g)

www.AutoDCSTech.com

Technical Specifications

Manufacturer Schneider Electric

Product Line TSX Micro PLCs

Part Number TSXP57203M

EAN 3595862023849

Weight 1.00 lbs (0.45 kg)

System Overhead 0.3 ms fast task, 1 ms master task

Memory Description Internal RAM: 224 KB program and 96 KB data with PCMCIA card; 96 KB program and data without PCMCIA card

PCMCIA Card 256 KB additional data storage

Execution Time per Instruction 0.19 μ s Boolean without PCMCIA card, 0.25 μ s Boolean with PCMCIA card

Number of Instructions per ms 2.1 Kinst/ms (with PCMCIA card: 65% Boolean + 35% fixed arithmetic), 3.71 Kinst/ms (without PCMCIA card: 65% Boolean + 35% fixed arithmetic)

Current Consumption 1650 mA, 5 V DC

Module Format Standard

Communication Module Processor Capacity 2 modules

Integrated Connection Type Ethernet TCP/IP RJ45, Serial link 2 female mini DIN RS485 19.2 kbit/s

Analogue I/O Processor Capacity 24 I/O

Discrete I/O Processor Capacity 512 I/O

Number of Racks 2 (12 slots), 4 (4/6/8 slots)

Internal RAM 96 KB data

Application Structure 1 mast

www.AutoDCSTech.com