

Schneider 170ADO35000 Manual

Brand	Schneider
Product Series	Schneider
Product Type	Discrete Output Module

Description

The 170ADO35000 is a discrete output module from Schneider Electric's Modicon Momentum series. It features 32 solid-state outputs, capable of handling a surge current of 5 A for brief durations of 1 ms, with an output voltage range of 0 to 24 V DC.

Technical specifications for 170ADO35000

Manufacturer Schneider Electric

Product Type Discrete Output Module

Product Line Modicon Momentum

Part Number 170ADO35000

UPC 785901308003

Weight 0.56 lbs (0.26 kg)

Outputs 32 Solid State

Surge Current 5 A, 1 ms duration

Voltage Drop <0.5 V at 0.5 A

Overload Protection Electronically protected

Insulation Voltage 4 kV IEC 801-2

Air Discharge Voltage 8 kV IEC 801-2

Radiated Immunity 10 V/m, 80-1000 MHz

Operating Temperature 0 to 60°C

Storage Temperature -40 to 85°C

Max Output Frequency 1 kHz operation

Installation Location Pollution Degree 2

Compliance Standards CSA, UL-approved

Output Voltage Range 0-24 V DC rated

Certifications CE, RoHS compliant

The Schneider Electric 170ADO35000 discrete output module operates within the Modicon Momentum series and is engineered for robust performance in control systems. It boasts a configuration of 32 solid-state outputs designed for reliability and efficiency. This module can manage a surge current of 5 A for a duration of 1 ms, ensuring strong responsiveness under high load conditions. The voltage drop during operation is kept under 0.5 V when delivering 0.5 A, which is advantageous for maintaining system integrity.

In terms of protection, the module is equipped with electronic overload safeguards, enhancing its durability and reliability. Insulation voltage has been rated at 4 kV according to IEC 801-2 standards, offering additional safety against electrical faults. Additionally, it supports an air discharge voltage of up to 8 kV, confirming its resilience in adverse conditions. The module also exhibits radiated immunity of 10 V/m across a frequency range of 80 to 1000 MHz, ensuring stable operation in electrically noisy environments.

Operating temperature for the 170ADO35000 extends from 0 to 60°C, making it suitable for a variety of environments. When not in use, it can withstand storage temperatures ranging from -40 to 85°C. The maximum output frequency that can be achieved is 1 kHz, which meets the demands of modern control applications.

Designed for installation in areas classified as Pollution Degree 2, the module is compliant with various industry standards, including CSA and UL certifications. Furthermore, it is CE and RoHS compliant, aligning with international regulatory requirements for safety and environmental impact. Overall, the 170ADO35000 is a reliable choice for discrete output control within various automation systems.

Technical Specifications

Manufacturer Schneider Electric
Product Type Discrete Output Module
Product Line Modicon Momentum
Part Number 170ADO35000
UPC 785901308003
Weight 0.56 lbs (0.26 kg)
Outputs 32 Solid State
Surge Current 5 A, 1 ms duration
Voltage Drop <0.5 V at 0.5 A
Overload Protection Electronically protected
Insulation Voltage 4 kV IEC 801-2
Air Discharge Voltage 8 kV IEC 801-2
Radiated Immunity 10 V/m, 100-1000 MHz
Operating Temperature 0 to 60°C
Storage Temperature -40 to 85°C
Max Output Frequency 1 kHz operation
Installation Location Pollution Degree 2
Compliance Standards CSA, UL-approved
Output Voltage Range 0-24 V DC rated
Certifications CE, RoHS compliant

www.AutoDCSTech.com