

Bently Nevada 200152-25-10 Manual

Brand	Bently Nevada
Product Series	200150&200151
Product Type	200151 - Accelerometer Interface Standard Cable,

Description

200152-25-10 | Accelerometer Interface Standard Cable,
Connector on Accelerometer End Only | Bently Nevada

Ordering Information :

Model: 200151 - Accelerometer Interface Standard Cable,
Connector on Accelerometer End Only
Cable length: -25= 25 meters

Coupling nut: -10 = Enhanced coupling nut. This option provides a better grip for tightening the cable to the accelerometer and is provided on the accelerometer end only (see Figure 12).

Minimum Bend Radius
200152 73.7 mm (2.9 in)

Operating

Temperature

Range

-20 °C to +100 °C (-4 °F to +212 °F)

These cables may be used at lower temperatures if the installation prevents the cable from flexing or bending. Flexing these cables at temperatures below -20 °C (-4 °F) may damage the cables.

Construction 4-conductor, 22 AWG with braided shield and drain wire (85% coverage, minimum), PVC outer jacket. Nickel-plated coupling nuts.

Seal Connectors provide an IP67 seal to transducers and mating hardware. Connectors are molded to the cable. The

addition of DC4 electrical insulating compound in the connectors provides additional protection against moisture during a thermal shock.

Temperature

Range

-55 °C to +121 °C (-67 °F to +250

°F)

Cure Time 24 hours

www.AutoDCSTech.com