

Mitsubishi FX3U-80MR-ES-A Manual

Brand	Mitsubishi
Product Series	Mitsubishi Pepperl+Fuchs Omron
Product Type	FX3U Series Programmable Controller

Description

FX3U-80MR-ES-A

Manufacturer : Mitsubishi Electric

Product No. : FX3U-80MR-ES-A

Product type : FX3U Series Programmable Controller

Integrated Inputs/Outputs : 80

Power Supply : 100-240 VAC

Integrated Inputs : 40

Integrated Outputs : 40

Output Type : Relay

Power Consumption W : 50

Series MELSEC-F SERIES

Type FX3U

Power Supply (V) 100-240

Current Type AC

Program Memory 64K STEPS

Program Memory Unit RAM

Integrated Digital Inputs 40

Integrated Digital Outputs 40

Output Type RELAY

Local I/O Points 256

Local + Remote I/O Points 384

Expandable YES

Cycle Time LD (ns) 65

Cycle Time MOV (ns) 642

USB OPTION

RS-422 1

Power Consumption (W) 50

Buffer Battery YES

Protection Class IP10

Min. Ambient Temperature (°C) 0

Max. Ambient Temperature (°C) 55

Product Dimensions & Weight

Width (mm) 285

Height (mm) 90

Depth (mm) 86

Weight (kg) 1,2

www.AutoDCSTech.com