

ABB AI910N Manual

Brand	ABB
Product Series	ABB
Product Type	N. For installation in safe (= non-hazardous) area

Description

ABB AI910N 3KDE175513L9100 Redundancy Module

The remote S900 I/O system can be installed in non-hazardous areas or directly in Zone 1 or Zone 2 hazardous area depending on the selected system variant. S900 I/O communicates with the control system level using the PROFIBUS DP standard. The I/O system can be installed directly in the field, therefore the costs for marshalling and wiring are reduced.

The system is sturdy, error-tolerant and easy to service. Integrated disconnection mechanisms allow replacement during operation, meaning that there is no need to interrupt the primary voltage in order to exchange the power supply units.

S900 I/O type N. For installation in safe (= non-hazardous) area.

AI910N Analog Input (AI4), input and power supply for 4...20 mA loop powered 2-wire transmitters.

Features and benefits

Redundancy (Power and Communication)

Hot Configuration in Run

Hot Swap functionality

Extended Diagnostic

Excellent configuration and diagnostics via FDT/DTM

G3 – coating for all components

Simplified maintenance with auto-diagnostics

Power supply for 4...20 mA loop powered 2-wire transmitters

Short and break detection

Electrical isolation between input / bus and input / power

Common return for all inputs

4 channels

General info

Article number 3KDE175513L9100

Type Analog Input

Number of channels 4

Signal type 4...20 mA

HART No

SOE N/A

Redundancy No

Intrinsic safety No

Mechanics S900

Environment and certification

CE mark Yes

Corrosive atmosphere ISA-S71.04 G3

Climatic operating conditions Relative humidity max. 93 % +/- 3 % at 40 °C

Max ambient temperature -20 °C...60 °C

RoHS compliance DIRECTIVE/2011/65/EU (EN 50581:2012)

WEEE compliance DIRECTIVE/2012/19/EU

WEEE category Small Equipment (No External Dimension More Than 50 cm)

Dimensions

Width 20 mm (0.79 in.)

Depth 104 mm (4.09 in.)

Height 104 mm (4.09 in.)

Weight 0.13 kg (0.29 lbs.)

www.AutoDCSTech.com