

Schneider BMXAMI0410 Manual

Brand	Schneider
Product Series	Sheet1
Product Type	Analog input module

Description

BMXAMI0410

analog input module M340 - 4 inputs - high speed

Main

Range of product Modicon X80

Product or component type Analog input module

Electrical connection 1 connector 20 ways

Input output isolation Isolated

Input level High level

Analogue input number 4

Analogue input type Current +/- 20 mA

Current 0...20 mA

Current 4...20 mA

Voltage +/- 10 V

Voltage +/- 5 V

Voltage 0...10 V

Voltage 0...5 V

Voltage 1...5 V

Complementary

Analog/Digital conversion 24 bits

Analogue input resolution 16 bits

Input impedance 10 MOhm

Permitted overload on inputs +/- 30 V +/- 10 V

+/- 30 V +/- 5 V

+/- 30 V 0...10 V

+/- 30 V 0...5 V

+/- 30 V 1...5 V

+/- 90 mA +/- 20 mA

+/- 90 mA 0...20 mA

+/- 90 mA 4...20 mA

Internal conversion resistor 250 Ohm

Precision of internal conversion
resistor

0.1 % - 15 ppm/°C

Type of filter First order digital filtering

Fast read cycle time 1 ms + 1 ms x number of channels used

Nominal read cycle time 5 ms for 4 channels

Measurement error <= 0.1 % of full scale +/- 10 V 0...60 °C

<= 0.1 % of full scale +/- 5 V 0...60 °C
<= 0.1 % of full scale 0...10 V 0...60 °C
<= 0.1 % of full scale 0...5 V 0...60 °C
<= 0.1 % of full scale 1...5 V 0...60 °C
<= 0.3 % of full scale +/- 20 mA 0...60 °C
<= 0.3 % of full scale 0...20 mA 0...60 °C
<= 0.3 % of full scale 4...20 mA 0...60 °C
0.075 % of full scale +/- 10 V 25 °C
0.075 % of full scale +/- 5 V 25 °C
0.075 % of full scale 0...10 V 25 °C
0.075 % of full scale 0...5 V 25 °C
0.075 % of full scale 1...5 V 25 °C
0.15 % of full scale +/- 20 mA 25 °C
0.15 % of full scale 0...20 mA 25 °C
0.15 % of full scale 4...20 mA 25 °C
Temperature drift 15 ppm/°C +/- 10 V
15 ppm/°C +/- 5 V
15 ppm/°C 0...10 V
15 ppm/°C 0...5 V
15 ppm/°C 1...5 V
30 ppm/°C +/- 20 mA
30 ppm/°C 0...20 mA
30 ppm/°C 4...20 mA
Recalibration Interval
Common mode between channels 120 dB
Digital value format +/- 32000 in user scale
+/- 10000 by default
Isolation voltage 300 V DC between channels
1400 V DC between channels and ground
1400 V DC between channels and bus
Measurement resolution 0.35 mV +/- 10 V
0.35 mV +/- 5 V
0.35 mV 0...10 V
0.35 mV 0...5 V
0.35 mV 1...5 V
0.92 µA +/- 20 mA
0.92 µA 0...20 mA
0.92 µA 4...20 mA
Maximum conversion value +/- 11.4 V +/- 10 V
+/- 11.4 V +/- 5 V
+/- 11.4 V 0...10 V
+/- 11.4 V 0...5 V
+/- 11.4 V 1...5 V
0...30 mA +/- 20 mA
0...30 mA 0...20 mA
0...30 mA 4...20 mA
Status LED 1 LED green RUN
1 LED per channel green channel diagnostic
1 LED red ERR
1 LED red I/O
Product weight 0.143 kg

www.AutoDCSTech.com

Current consumption 150 mA at 3.3 V DC

45 mA at 24 V DC

Environment

Vibration resistance 3 gn

Shock resistance 30 gn

Ambient air temperature for storage -40...85 °C

Ambient air temperature for operation 0...60 °C

Relative humidity 5...95 % without condensation

IP degree of protection IP20

Product certifications Merchant Navy

RCM

UL

CSA

EAC

CE

Standards EN/IEC 61131-2

CSA C22.2 No 61010-2-201

EN/IEC 61010-2-201

UL 61010-2-201

Protective treatment TC

Operating altitude 0...2000 m

2000...5000 m (with derating factor)

Offer Sustainability

Sustainable offer status Green Premium product

RoHS (date code: YYWW) Compliant - since 0722 - Schneider Electric declaration of conformity

www.AutoDCSTech.com