

Schneider BMXP342020 Manual

Brand	Schneider
Product Series	BME
Product Type	Processor module

Description

processor module M340, max 1024 discrete and 256 analog I/O, Modbus, Ethernet
BMXP342020

Main

Range of Product

Modicon M340 automation platform

Product or Component Type

Processor module

Concept

Transparent Ready

CANopen

Number of racks

4

Number of slots

11

Discrete I/O processor capacity

1024 I/O multi-rack configuration

704 I/O single-rack configuration

Analogue I/O processor capacity

256 I/O multi-rack configuration

66 I/O single-rack configuration

Number of application specific channel

36

Monitoring

Diagnostic counters Modbus

Event counters Modbus

Complementary

Control channels

Programmable loops

Integrated connection type

Non isolated serial link RJ45 character mode asynchronous in baseband, RS232C 2 twisted shielded pairs 0.3...19.2 kbit/s full duplex

Non isolated serial link RJ45 character mode asynchronous in baseband, RS485 1 twisted shielded pair 0.3...19.2 kbit/s half duplex

Non isolated serial link RJ45, master/slave Modbus, RTU/ASCII asynchronous in baseband, RS232C 1 twisted shielded pair 0.3...19.2 kbit/s half duplex

Non isolated serial link RJ45, master/slave Modbus, RTU/ASCII asynchronous in baseband, RS485 1 twisted shielded pair 0.3...19.2 kbit/s half duplex

USB port 12 Mbit/s

Ethernet TCP/IP RJ45 1 twisted pair 10/100 Mbit/s

Communication module processor capacity

2 Ethernet communication module
4 AS-Interface module
embedded communication service
Bandwidth management, Ethernet TCP/IP
Data Editor, Ethernet TCP/IP
Modbus TCP messaging, Ethernet TCP/IP
Rack Viewer, Ethernet TCP/IP
SNMP network administrator, Ethernet TCP/IP
Port Ethernet
10BASE-T/100BASE-TX
Number of devices per segment
0...32character mode)
0...32Modbus)
Number of devices
2 point-to-point character mode
2 point-to-point Modbus
Bus length
0...32.8 ft (0...10 m) serial link non isolated character mode segment
0...32.8 ft (0...10 m) serial link non isolated Modbus segment
0...3280.8 ft (0...1000 m) serial link isolated character mode segment
0...3280.8 ft (0...1000 m) serial link isolated Modbus segment
0...49.2 ft (0...15 m) character mode point-to-point
0...49.2 ft (0...15 m) Modbus point-to-point
Maximum tap links length
<49.2 ft (15 m) serial link non isolated character mode segment
<49.2 ft (15 m) serial link non isolated Modbus segment
<131.2 ft (40 m) serial link isolated character mode segment
<131.2 ft (40 m) serial link isolated Modbus segment
Number of addresses
0...248 character mode
0...248 Modbus
Requests
1 K data bytes per request character mode
252 data bytes per RTU request Modbus
504 data bytes per ASCII request Modbus
Control parameter
One CRC on each frame (RTU) Modbus
One LRC on each frame (ASCII) character mode
One LRC on each frame (ASCII) Modbus
Memory description
Supplied memory card (BMXRMS008MP) backup of programs, constants, symbols and data
Internal RAM 4096 kB
Internal RAM 256 kB data
Internal RAM 3584 kB program constants and symbols
Supplied memory card (BMXRMS008MP) activation of standard web server, class B10
Maximum size of object areas
256 kB unlocated internal data
32634 %Mi located internal bits
Default size of object areas
1024 %MWi internal words located internal data
256 %KW constant words located internal data

512 %Mi located internal bits

Application structure

1 cyclic/periodic master task

1 periodic fast task

No auxiliary task

64 event tasks

Execution time per instruction

0.12 μ s Boolean

0.17 μ s double-length words

0.25 μ s single-length words

1.16 μ s floating points

Number of instructions per ms

6.4 Kinst/ms 65 % Boolean + 35 % fixed arithmetic

8.1 Kinst/ms 100 % Boolean

System overhead

0.13 ms fast task

0.7 ms master task

Current consumption

95 mA 24 V DC

Supply

Internal power supply via rack

Marking

CE

Status LED

1 LED (Green) activity on Ethernet network (ETH ACT)

1 LED (Green) processor running (RUN)

1 LED (Green) status of Ethernet network (ETH STS)

1 LED (Red) data rate (ETH 100)

1 LED (Red) I/O module fault (I/O)

1 LED (Red) memory card fault (CARD ERR)

1 LED (Red) processor or system fault (ERR)

1 LED (Yellow) activity on Modbus (SER COM)

Product Weight

0.452 lb(US) (0.205 kg)

Environment

Ambient Air Temperature for Operation

32...140 °F (0...60 °C)

Relative Humidity

10...95 % without condensation

IP Degree of Protection

IP20

Protective treatment

TC

Directives

2014/35/EU - low voltage directive

2014/30/EU - electromagnetic compatibility

Product certifications

CE

UL

CSA

RCM

EAC
Merchant Navy
Standards
EN 61131-2
EN/IEC 61010-2-201
UL 61010-2-201
CSA C22.2 No 61010-2-201
IACS E10
EN/IEC 61000-6-5, interface type 1 and type 2
EN/IEC 61850-3, location G
Environmental characteristic
Hazardous location class I division 2
Ordering and shipping details
Category
US1PC3418160
Discount Schedule
PC34
GTIN
3595863910711
Returnability
Yes
Country of origin
FR
Packing Units
Unit Type of Package 1
PCE
Nbr. of units in pkg.
1
Package 1 Height
2.17 in (5.500 cm)
Package 1 Width
4.33 in (11.000 cm)
Package 1 Length
4.53 in (11.500 cm)
Package weight(Lbs)
8.642 oz (245.000 g)
Unit Type of Package 2
S02
Number of Units in Package 2
15
Package 2 Height
5.91 in (15.000 cm)
Package 2 Width
11.81 in (30.000 cm)
Package 2 Length
15.75 in (40.000 cm)
Package 2 Weight
8.854 lb(US) (4.016 kg)
Unit Type of Package 3
P06
Number of Units in Package 3

www.AutoDCSTech.com

240

Package 3 Height

29.53 in (75.000 cm)

Package 3 Width

23.62 in (60.000 cm)

Package 3 Length

31.50 in (80.000 cm)

Package 3 Weight

163.707 lb(US) (74.256 kg)

www.AutoDCSTech.com