

FANUC VFS15-4022PL1-W1 Manual

Brand	FANUC
Product Series	FANUC
Product Type	-

Description

Toshiba VFS15-4022PL1-W1 Variable Torque VFD 460 Volt Three Phase 3 HP

Description

Toshiba VFS15-4022PL1-W1 Variable Frequency Drive with 460 Volt Three Phase Input Voltage, 460 Volt Three Phase Output Voltage, 5.5 Amp Output Amps, 3 HP Output Horsepower, Variable Torque.

Specifications

VFD Torque

Variable Torque

VFD Application

Centrifugal Pump

VFD Application

Fan

VFD Application

Blower

VFD Horsepower Output

3 HP

VFD Amperage Output

5.5 Amp

VFD Input Voltage

460 Volt Three Phase

VFD Output Voltage

460 Volt Three Phase

Manufacturer

Toshiba

Features

IP20 Enclosure

Wall-Mount

Past Trip Monitoring: Stores the Last Eight Faults in Succession, Along with At-Trip Operation Data

Rotary Encoder

EOI: Four-Digit/Seven-Segment LED Display

Ambient Temperature: 14° to 122°F (-10° to 50°C)

Humidity: 95% Non-Condensing

Altitude: Up to 1000 Meters without Derate

Two-Wire RS485 Communication Port

Compliances: UL Listed in US & Canada, CSA, & CE

VARIABLE SPEED DRIVE

VF-S15 SERIES

SINUSOIDAL PWM CONTROL

www.AutoDCSTech.com

0.1 TO 500.0HZ

DEFAULT SETTING: 0.5 TO 60HZ

MAXIMUM FREQUENCY: 30 TO 500HZ

THREE PHASE

460 VAC

3 HP

OPERATION PANEL

BUILT-IN HIGH-ATTENUATION EMC FILTER

www.AutoDCSTech.com