

Bently Nevada 200151-40-02-02 Manual

Brand	Bently Nevada
Product Series	200150&200151
Product Type	200151 - Accelerometer Interface Standard Cable, Connectors on Both Ends

Description

200151-40-02-02 | Accelerometer Standard Cable | Bently Nevada

Ordering Information :

Model: 200151 - Accelerometer Interface Standard Cable, Connectors on Both Ends

Cable length: -40 = 4.0 meters

Armor option: -02 = Blue cable without armor

Coupling nut: 02 = Nylon coupling nut

Minimum Bend Radius

200151 63.5 mm (2.5 in)

Operating

Temperature

Range

-20 °C to +100 °C (-4 °F to +212

°F)

These cables may be used at lower temperatures if the installation prevents the cable from flexing or bending. Flexing these cables at temperatures below -20 °C (-4 °F) may damage the cables.

Construction 4-conductor, 22 AWG with braided shield and drain wire (85% coverage, minimum), PVC outer jacket. Nickel-plated coupling nuts.

Seal Connectors provide an IP67 seal to transducers and mating hardware. Connectors are molded to the cable. The addition of DC4 electrical insulating compound in the connectors provides additional protection against moisture during a thermal

shock.

Temperature

Range

-55 °C to +121 °C (-67 °F to +250

°F)

Cure Time 24 hours

www.AutoDCSTech.com