

Schneider TSXPSY2600M Manual

Brand	Schneider
Product Series	Schneider
Product Type	Power Supply Module

Description

The TSXPSY2600M from Schneider Electric is a power supply module designed for TSX Micro PLCs. This unit supports primary voltage input of 24 V DC, with an operational capacity to handle inrush currents of up to 100 A at this voltage level.

Technical specifications for TSXPSY2600M

Manufacturer Schneider Electric

Product Line TSX Micro PLCs

Part Number TSXPSY2600M

EAN 3389110725605

Weight 1.00 lbs (0.45 kg)

Operating Altitude 0 to 2000 meters

Protective Treatment TC

IP Degree of Protection IP20

Secondary Power 15 W at 5 V DC, 15 W at 24 V DC

Total Useful Secondary Power 30 W

Inrush Current 100 A at 24 V

Input Current ≤ 1500 mA at 24 V

Primary Voltage 24 V DC (19.2 to 30 V)

Module Type Power Supply Module

Current at Secondary Voltage 0.6 A at 24 V DC (relay power supply), 3 A at 5 V DC

Protection Type Internal fuse (3.5 A, 5 x 20 mm, time-delayed), overload protection, overvoltage protection, short-circuit protection

Local Signalling 1 LED for presence of voltages (green), 1 LED for battery fault (red)

Operating Temperature 0 to 60 °C

Storage Temperature -25 to 70 °C

Relative Humidity 10 to 95% without condensation for operation, 5 to 95% without condensation for storage

Description

The Schneider Electric TSXPSY2600M is a power supply module tailored for the TSX Micro PLC series. It can effectively operate at an altitude of 0 to 2000 meters. This unit features an IP20 rating, making it suitable for areas without exposure to moisture or dust. Designed for robust performance, this device delivers a primary input voltage of 24 V DC, within a range of 19.2 to 30 V.

The module outputs secondary power at 15 W for both 5 V DC and 24 V DC, cumulating to a total useful secondary power of 30 W. The TSXPSY2600M allows a secondary current of 0.6 A at 24 V DC and 3 A at 5 V DC. It can manage an inrush current of 100 A at 24 V. The input current is capped at 1500 mA at 24 V.

For safety, this power supply module incorporates several protection features. It includes an internal time-delayed fuse rated at 3.5 A, overload protection, overvoltage prevention, and short-circuit protection to safeguard the connected equipment.

Local signaling is facilitated by two LEDs, with a green LED indicating voltage presence and a red LED signaling battery faults. The module operates reliably within a temperature range of 0 to 60 °C and can be stored in temperatures between -25 and 70 °C.

Additionally, it maintains functionality in relative humidity levels of 10 to 95% (without condensation for operation) and can be safely stored under conditions of 5 to 95% humidity (also without condensation). Overall, the TSXPSY2600M serves as a dependable power source for various applications.

Range of Product

Modicon Premium Automation platform

Product or Component Type

Power supply module

Complementary

Primary voltage

100...240 V AC 85...264 V

Network Frequency

50/60 Hz

Network frequency limits

47...63 Hz

Input current

300 mA 240 V

500 mA 100 V

Inrush current

37 A 100 V

75 A 240 V

I^2t on activation

0.63 A².s 100 V

2.6 A².s 240 V

I_t on activation

0.034 A.s 100 V

0.067 A.s 240 V

Protection type

Internal fuse 4 A 5 x 20 mm time-delayed primary circuit

Overload protection secondary circuit

Overvoltage protection secondary circuit

Short-circuit protection secondary circuit

Total useful secondary power

26 W

Secondary power

15 W 24 V DC

25 W 5 V DC

Current at secondary voltage

0.5 A 24 V DC sensor power supply

0.6 A 24 V DC relay power supply

5 A 5 V DC

Insulation resistance

≥ 100 MOhm primary/ground

≥ 100 MOhm primary/secondary

Marking

CE

Local signalling

1 LED (green) for presence of sensor voltage (24V)

1 LED (green) for presence of voltages (OK)

1 LED (red) for battery fault (BAT)

Module format

www.AutoDCSTech.com

Standard

Net Weight

1.12 lb(US) (0.51 kg)

Environment

Immunity to microbreaks

10 ms

Dielectric strength

2000 V primary/earth

2000 V primary/secondary

Standards

CSA C22.2 No 142

CSA C22.2 No 213 Class I Division 2 Group A

IEC 61131-2

UL 508

89/336/EEC

CSA C22.2 No 213 Class I Division 2 Group B

92/31/EEC

93/68/EEC

CSA C22.2 No 213 Class I Division 2 Group D

73/23/EEC

CSA C22.2 No 213 Class I Division 2 Group C

Product Certifications

RMRS

BV

RINA

GL

ABS

DNV

LR

Ambient Air Temperature for Operation

32...140 °F (0...60 °C)

Ambient Air Temperature for Storage

-13...158 °F (-25...70 °C)

Relative Humidity

10...95 % without condensation for operation

5...95 % without condensation for storage

Operating altitude

0...6561.68 ft (0...2000 m)

Protective treatment

TC

IP Degree of Protection

IP20

Pollution degree

2

Ordering and shipping details

Category

US1PC2222558

Discount Schedule

PC22

GTIN

3389110725605

Returnability

No

Packing Units

Unit Type of Package 1

PCE

Nbr. of units in pkg.

1

Package 1 Height

2.4 in (6.0 cm)

Package 1 Width

7.09 in (18.0 cm)

Package 1 Length

10.2 in (26.0 cm)

Package weight(Lbs)

21.8 oz (619.0 g)

Technical Specifications

Manufacturer Schneider Electric

Product Line TSX Micro PLCs

Part Number TSXPSY2600M

EAN 3389110725605

Weight 1.00 lbs (0.45 kg)

Operating Altitude 0 to 2000 meters

Protective Treatment TC

IP Degree of Protection IP20

Secondary Power 15 W at 5 V DC, 15 W at 24 V DC

Total Useful Secondary Power 30 W

Inrush Current 100 A at 24 V

Input Current ≤ 1500 mA at 24 V

Primary Voltage 24 V DC (19.2 to 30 V)

Module Type Power Supply Module

Current at Secondary Voltage 0.6 A at 24 V DC (relay power supply), 3 A at 5 V DC

Protection Type Internal fuse (3.5 A, 5 x 20 mm, time-delayed), overload protection, overvoltage protection, short-circuit protection

Local Signalling 1 LED for presence of voltages (green), 1 LED for battery fault (red)

Operating Temperature 0 to 60 °C

Storage Temperature -25 to 70 °C

Relative Humidity 10 to 95% without condensation for operation, 5 to 95% without condensation for storage