

Mitsubishi FX3U-64MT-ES-A Manual

Brand	Mitsubishi
Product Series	Mitsubishi Pepperl+Fuchs Omron
Product Type	Main Units with 64 I/O

Description

FX3U-64MT-ES-A Manufacturer : Mitsubishi Electric

Product No : FX3U-64MT / ES-A

Product type : Main Units with 64 I/O

FX3U-64MT / ES-A is the third generation in their family FX Series PLC is a compact PLC and successful form of Mitsubishi Electric.

The system "bus adapter" supplemented for bus systems useful for extended special features and block network communications.

Mitsubishi PLC FX3U-64MT / ES-A

Maximum Likelihood can expand up to 10 blocks on the new bus

The CPU with 64 I / O: 32 input and 32 output transistor (Sink)

Power supply: 100-240 VAC.

Power: 45 W

Memory program: 64,000 Steps

Integrated real-time clock.

Counter: 235

Timer: 512

Integrated portal RS232C, RS485.

Cable connection: FX-USB-AW, USB-SC09, USB-SC09

Origin: Mitsubishi - Japan

Main Unit

Series MELSEC-F SERIES

Type FX3U

Power Supply (V) 100-240

Current Type AC

Program Memory 64K STEPS
Program Memory Unit RAM
Integrated Digital Inputs 32
Integrated Digital Outputs 32
Output Type TRANSISTOR
Output Logic SINK
Local I/O Points 256
Local + Remote I/O Points 384
Expandable YES
Cycle Time LD (ns) 65
Cycle Time MOV (ns) 642
RS-422 1
Power Consumption (W) 45
Buffer Battery YES
Protection Class IP10
Min. Ambient Temperature (°C) 0
Max. Ambient Temperature (°C) 55
Product Dimensions & Weight
Width (mm) 220
Height (mm) 90
Depth (mm) 86
Weight (kg) 1

www.AutoDCSTech.com