

FX3SA-10MT-CM Manual

Brand	-
Product Series	Mitsubishi Pepperl+Fuchs Omron
Product Type	relay

Description

FX3SA-10MT-CM | Mitsubishi Electric | Programmable Logic Controller

MITSUBISHI FX3SA-10MT-CM Product information and technical parameters :

Brand: MITSUBISHI

Name: PLC

Model: FX3SA-10MT-CM

Input and output points: 10 points.

Power supply: AC100-240V.

Input points: 6 points.

Output points: 4 points.

Output form: transistor output (drain).

Power consumption: 19W.

Weight: 0.3KG.

Outline dimension: 60x90x75mm.

A new application model.

FX3SA is a basic model on the basis of the basic performance of FX1S above the expansion of the expansion of the new model.

FX3SA is applicable to all kinds of fields of small scale equipment which need to simulate the quantity and function of MODBUS and Ethernet.

Basic models suitable for small scale control.

Compact but powerful,

At the same time, the analog quantity and communication function, etc..

Max input / output points: 14 points.

Supply voltage: 100 - 240VAC.

Input points: 8 points.

Output points: 6 points.

Output type: relay.

Power consumption (W): 32.

Weight (kg):0.4.

Size (WxHxD) mm:90x90x75.

Rich functionality.

FX series of products are rich in variety, users can be based on cost or application,

Choose the most suitable product FX3SA-10MT-CM. Will find a suitable model for the user site FX3SA-10MT-CM

Terminal row type standard machine with extended input output

Can also be less of a system with analog or communication, etc..

CPU, power supply, input and output integration.

Display module or function expansion board can be less installed.

In addition, you can also reduce the input output or special module FX3SA-10MT-CM.

Built in 8000 step EPROM memory.

No battery. Maintenance free.

Overseas oriented products meet all kinds of international standards. Max input / output points: 24 points.

Power supply voltage: DC24V.

Input points: 14 points.

Output points: 10 points.

Output type: relay.

Power consumption (W): 32.

Weight (kg):0.5.

Size (WxHxD) mm:90x90x75.

FX1N series is a very powerful micro PLC, can be extended to up to 128 I/O points,

And can increase the special function module or the expansion board FX3SA-10MT-CM.

Communication and data link function options make FX1N in the volume, communication and special function modules and other important applications is very perfect.

A PLC unit can output 2 100KHz pulses at the same time,

PLC is equipped with 7 special positioning instructions,

Including zero return, absolute position readout, absolute or relative drive, and special pulse output control. Total points: 24 points.

Input points: 14 points.

Output points: 10 points FX3SA-10MT-CM.

Voltage: AC220V.

Output type: relay.

Outline dimension: 90*75*90.

FX1N series is a very powerful micro PLC,

Can be extended to up to 128 I/O points.

And can increase the special function module or the expansion board.