

Mitsubishi FX3U-64MR-ES-A Manual

Brand	Mitsubishi
Product Series	Mitsubishi Pepperl+Fuchs Omron
Product Type	Main Units with 64 I/O

Description

FX3U-64MR-ES-A Mitsubishi Electric | Main Units with 64 I/O

Manufacturer : Mitsubishi Electric

Product No. : FX3U-64MR/ES-A

Product type : Main Units with 64 I/O

MAX.NUMBER INPUT/OUTPUT: 64

NO. OF INPUTS: 32

NO. OF OUTPUTS: 32

TYPE OF OUTPUT: Relay

POWER SUPPLY: 100-240V AC

POWER CONSUMPTION: 45W

DIMENSIONS (WxHxD) [mm]: 220x90x86

Actual Dimension Standard Packing Box HXWXD (cm) : 15 x 20 x 87

Series MELSEC-F SERIES

Type FX3U

Power Supply (V) 100-240

Current Type AC

Program Memory 64K STEPS

Program Memory Unit RAM

Integrated Digital Inputs 32

Integrated Digital Outputs 32

Output Type RELAY

Local I/O Points 256

Local + Remote I/O Points 384

Expandable YES

Cycle Time LD (ns) 65

Cycle Time MOV (ns) 642

USB OPTION

RS-422 1

Power Consumption (W) 45

Buffer Battery YES

Protection Class IP10

Min. Ambient Temperature (°C) 0

Max. Ambient Temperature (°C) 55

Product Dimensions & Weight

Width (mm) 220

Height (mm) 90

Depth (mm) 86

Weight (kg) 1