

GE IC200MDL740 Manual

Brand	GE
Product Series	Versamax
Product Type	-

Description

The IC200MDL740 Discrete Output Module is a 12/24 Volts DC Versamax Positive Logic Output Module made by GE Fanuc. It has 16 discrete outputs, 10.2 to 30 Volts DC, 12/24 Volts DC nominal of external power supply voltage, and, 45 milliamps of backplane current consumption.

Technical specifications for IC200MDL740

Brand GE Fanuc

Series Versamax

Part Number IC200MDL740

Product Description Discrete Output Module

Module ID FFFF8080

Number of Points 16 Outputs

Number of groups 1

Output Voltage 10.2 to 30 VDC, 12/24 VDC nominal

Group to Group Isolation None

Point to Point Isolation None

LED Indicators One LED per point, and "OK" and "FLD PWR" LEDs

Backplane Current Consumption 5 Volts, 45 milliamps

Fuse None

External Power Supply 10.2 to 30 VDC, 12/24 VDC nominal

The IC200MDL740 Discrete Output Module is a GE Fanuc 12/24 Volts DC Versamax Positive Logic Output Module that has 1 group of 16 sourcing type outputs. It features a rack mounting option, and a compact design with hot insertion facilities which helps the users to replace it easily without changing the field wiring. The IC200MDL740 Discrete Output Module has LEDs to indicate the status of each of the output points. There are 3 types of carriers available for easily installing or replacing the output module in a system without interrupting the operation. It has a configurable filter time, 0.2 milliseconds of maximum on response time, and 1.0 milliseconds of maximum off response time. It also provides an external power supply to the load side and it operates with backplane power.

The IC200MDL740 DC Positive Logic Output Module has one group of outputs with DC+ and DC- terminals. An external suppression circuit must be used with inductive loads at the output. This external suppression circuit can be connected across the actual load or to each output point which drives the inductive load. It is recommended to use a shorting bar with 2 Amps of current carrying capacity with the B Terminal to add extra bused terminals. A wide range of carriers allows the users to install the right carrier without using any tools. These easy connection facilities reduce the training time and lifecycle costs necessary to use this output module. It also comes with configuration software to easily perform the hardware and network configurations. The IC200MDL740 Discrete Output Module is a universally distributed product that is designed for industrial and commercial automation as well as for industrial control applications.

Technical Specifications

Brand GE Fanuc

Series Versamax

Part Number IC200MDL740

Product Description Discrete Output Module

Module ID FFFF8080

Number of Points 16 Outputs

Number of groups 1

Output Voltage 10.2 to 30 VDC, 12/24 VDC nominal

Group to Group Isolation None

Point to Point Isolation None

LED Indicators One LED per point, and "OK" and "FLD PWR" LEDs

Backplane Current Consumption 5 Volts, 45 milliamps

Fuse None

External Power Supply 10.2 to 30 VDC, 12/24 VDC nominal

The IC200MDL740 Discrete Output Module is a GE Fanuc 12/24 Volts DC Versamax Positive Logic Output Module that has 1 group of 16 sourcing type outputs. It features a rack mounting option, and a compact design with hot insertion facilities which helps the users to replace it easily without changing the field wiring. The IC200MDL740 Discrete Output Module has LEDs to indicate the status of each of the output points. There are 3 types of carriers available for easily installing or replacing the output module in a system without interrupting the

www.AutoDCSTech.com