

# ABB V18345-1010261001 Manual

Brand	ABB
Product Series	Sheet27
Product Type	Valve Positioner

## Description

V18345-1010261001 | ABB | Valve Positioner

Manufacturer : ABB

Product No. :V18345-1010261001

Product type : Valve Positioner

V18345 : TZIDC = intelligent, configurable with indicator and operator panel

Case / Mounting : 1 = Case made of aluminium, varnished, protection IP 65 (NEMA 4X) for mounting to linear actuators acc. to DIN/IEC 534 / NAMUR or to rotary actuators acc. to VDI/VDE 3845 also ready for integral mounting

Input / communication port : 1 = Input 4 ... 20 mA, two-wire with connector plug for LKS adapter

Explosion protection : 0 = without

Output / safe position (in case of an electrical power failure) : 1 = Single acting, fail safe

Connections : 6 = Cable: Thread M20 x 1.5, Air pipe Thread G 1/4

Option modules for analog or digital position feedback : 1 = Plug-in module analog position feedback (sign. range 4 ... 20 mA)

Optional mechanical kit for digital position feedback : 0 = without

Design (varnish / coding) : 1 = Standard

Output signal (two-wire technology) Nominal range : 4 ... 20 mA

Digital input : Control voltage 0 ... 5 V DC logical switching state "0" 11 ... 30 V DC logical switching state "1"

Digital output (control circuit to DIN 19234/NAMUR) Supply voltage : 5 ... 11 V DC

Supply pressure : 1.4 ... 6 bar (20 ... 90 psi)

Air consumption : < 0.03 kg/h / 0.015 scfm (independent of supply pressure)

Housing Material/Protections : Aluminum, protection class IP 65 / NEMA 4X

Surface/color : Electrostatic dipping varnish with epoxy resin, stove-hardened. Case varnished black, RAL 9005, matte, housing cover Pantone 420.

Pneumatic connections : Threads G 1/4 or 1/4-18 NPT

Weight : 1.7 Kg

### Environmental capabilities

#### Ambient temperature

\_x0001\_40 °C to +85 °C for operation, storage and transport

\_x0001\_25 °C to +85 °C with proximity switches SJ2\_x0001\_S1N (NO)

#### Relative humidity

Operational (with closed housing and air supply switched on):

95 % (annual average), condensation permissible

Transport and storage:

75 % (annual average), non\_x0001\_condensing

#### Case

#### Material/Protections

Aluminum, protection class IP 65 / NEMA 4X

#### Surface/color

Electrostatic dipping varnish with epoxy resin, stove\_x0001\_hardened

Case varnished black, RAL 9005, matt,

Cap Pantone 420

Electrical connections

Screw terminals:

max. 1.0 mm<sup>2</sup> for options, max. 2.5 mm<sup>2</sup> for analog signal

NOTICE: Do not expose the terminals to strain!

Cable entry:

2 threads 1/2\_x0001\_14 NPT or M20x1.5

(1 with cable gland and 1 with pipe plug)

[www.AutoDCSTech.com](http://www.AutoDCSTech.com)