

Schneider BMEP582040 Manual

Brand	Schneider
Product Series	BME
Product Type	Processor module

Description

standalone processor, Modicon M580, 8MB, 61 Ethernet devices, 8 remote IO racks of X80 [TAA]

BMEP582040

Main

Range of Product

Modicon M580

Product or Component Type

Processor module

Complementary

Number of racks

4

Local I/O processor capacity (discrete)

2048 I/O

Local I/O processor capacity (analog)

512 I/O

Number of application specific channel (local rack)

72

Application specific I/O

Serial link

Counter

Accurate time stamping

HART

Motion control

SSI encoder

Checks

Process control

Control channels

Programmable loops

Integrated connection type

1 Ethernet TCP/IP service port

2 Ethernet TCP/IP device network

USB type mini B

Number of remote I/O station

8 - 2 remote drop

Number of distributed equipment

64

Communication module processor capacity

2 Ethernet communication module

16 AS-Interface module

Communication Service

DIO scanner
RIO scanner
Memory description
Expandable flash, 4 GB data storage
Integrated RAM, 10 kB system memory
Integrated RAM, 8 MB program process
Integrated RAM, 768 kB data process
Integrated RAM, 2 MB program safety
Integrated RAM, 512 kB data safety
Application structure
64 event tasks
2 auxiliary tasks
1 cyclic/periodic master task
1 periodic fast task
Cybersecurity
Achilles certified
DoS prevention
IPSec
SNMP logging
Syslog protocol support
Transport layer security
Audit trail
Embedded firewall
Firmware signature
Password protection
Port hardening
Secure communication (HTTPS)
Security log
Number of instructions per ms
30 Kinst/ms 65 % Boolean + 35 % fixed arithmetic
40 Kinst/ms 100 % Boolean
Current consumption
270 mA 24 V DC
MTBF reliability
775000 H
Marking
CE
Environment
Vibration resistance
3 gn
Shock resistance
15 gn
Ambient Air Temperature for Operation
32...140 °F (0...60 °C)
Ambient Air Temperature for Storage
-40...185 °F (-40...85 °C)
Operating altitude
0...6561.68 ft (0...2000 m)
2000...5000 m with derating factor
Relative humidity
5...95 % 131 °F (55 °C) without condensation

www.AutoDCSTech.com

IP Degree of Protection

IP20

Directives

2014/35/EU - low voltage directive

2014/30/EU - electromagnetic compatibility

Product certifications

CE

UL

CSA

RCM

EAC

Merchant Navy

Standards

IEC 61131-2

IEC 61010-2-201

UL 61010-2-201

CSA C22.2 No 61010-2-201

IACS E10

EN/IEC 61000-6-5, interface type 1 and type 2

EN/IEC 61850-3, location G

Environmental characteristic

Safety

Corrosion resistance

Salt mist

Dust resistant

Hazardous location class I division 2

Supply

Internal power supply via rack

Status LED

1 LED (Green) processor running (RUN)

1 LED (Red) processor or system fault (ERR)

1 LED (Red) I/O module fault (I/O)

1 LED (Green) download in progress (DL)

1 LED (Red) memory card or CPU flash fault (BACKUP)

1 LED (green/red) ETH MS (Ethernet port configuration status)

1 LED (green/red) Eth NS (Ethernet network status)

1 LED (Green) processor in safety mode (SRUN)

1 LED (Green) processor in maintenance mode (SMOD)

1 LED (Red) I/O values overridden by user (FORCED IO)

Net Weight

1.872 lb(US) (0.849 kg)

Ordering and shipping details

Category

US1PC3418161

Discount Schedule

PC34

GTIN

3595864174426

Returnability

Yes

Country of origin

www.AutoDCSTech.com

FR

Packing Units

Unit Type of Package 1

PCE

Nbr. of units in pkg.

1

Package 1 Height

3.62 in (9.200 cm)

Package 1 Width

7.01 in (17.800 cm)

Package 1 Length

9.92 in (25.200 cm)

Package weight(Lbs)

30.829 oz (874.000 g)

Unit Type of Package 2

S03

Number of Units in Package 2

6

Package 2 Height

11.81 in (30.000 cm)

Package 2 Width

11.81 in (30.000 cm)

Package 2 Length

15.75 in (40.000 cm)

Package 2 Weight

12.421 lb(US) (5.634 kg)

www.AutoDCSTech.com