

ABB CI871A Manual

Brand	ABB
Product Series	ABB
Product Type	-

Description

The CI871A is an AC 800M communication interface that connects to the PROFINET IO devices through Ethernet. The TP867 Baseplate has two RJ45 Ethernet connectors, but only the CH1 connector that supports 100Mbps is used for PROFINET IO connection. The Ethernet cable must be connected to the PROFINET IO network through an Ethernet switch.

The CI871 expansion unit contains the CEX-Bus logic, a communication unit, and a DC/DC converter that supplies the required voltage from +24 V supply through the CEX-Bus.

The CI871A module will only work with System 800xA 6.0.3.3, 6.1.1 and subsequent versions

Features and benefits

Connects PROFINET IO devices through Ethernet

General info

Article number 3BSE092693R1

Communication protocol PROFINET IO

Master or slave Master

Transmission speed 10/100 Mbit/s

Line redundancy No

Module redundancy Yes

Hot Swap Yes

Used together with HI Controller Yes

Detailed data

Max units on CEX bus 12

Connector RJ-45 female (8-pin)

24 V consumption typ. typ 160 mA

Environment and certification

Temperature, Operating +5 to +55 °C (+41 to +131 °F)

Temperature, Storage -40 to +70 °C (-40 to +158 °F)

Altitude 2000 m according to IEC/EN 61131-2

Pollution degree Degree 2 according to IEC/EN 61131-2

Corrosion protection G3 compliant to ISA 71.04

Relative humidity 5 to 95 %, non-condensing

Protection class IP20 according to EN60529, IEC 529

CE- marking Yes

Electrical Safety UL 61010-1, UL 61010-2-201

Hazardous location UL 60079-15, cULus Class 1, Zone 2, AEx nA IIC T4, ExnA IIC T4Gc X

Marine certificates DNV-GL, (Pending: ABS, BV, LR)

RoHS compliance DIRECTIVE/2011/65/EU (EN 50581:2012)

WEEE compliance DIRECTIVE/2012/19/EU

Dimensions

Width 59 mm (2.3 in.)
Height 185 mm (7.3 in.)
Depth 127.5 mm (5.0 in.)
Weight (including base) 700 g (1.5 lbs)

www.AutoDCSTech.com