

Honeywell 2MLR-AC22 Manual

Brand	Honeywell
Product Series	Honeywell
Product Type	)UL approved - DC power:125V/10A (Time-lag type) UL approved

Description

2MLR-AC22 | Honeywell MasterLogic-200 | Power Supply Modules

Manufacturer : Honeywell

Product Number : 2MLR-AC12 Rated input voltage 220 VAC

Input voltage range 176V~264VAC

Input frequency 50 / 60 Hz (47 ~ 63 Hz)

Max. input power 110 VA / 42 W

Inrush current 20A peak and lower (within 8 ms)

Efficiency 65% or higher

Input fuse Built in (not replaceable by a user) - AC power: 250V/3.15A (Time-lag Type) UL approved - DC power: 125V/10A (Time-lag type) UL approved

Allowed instantaneous interruption within 20 ms

Output voltage 5VDC ($\pm 2\%$)

Output current 5.5A

Output power 27.5W @ 55°C

Over current protection 6.0A~13.0A

Purpose RUN contact

Rated switching voltage/current 24VDC, 0.5A

Min. switching load 5VDC, 1 mA

Response time Off→On/ On→Off: 10 ms and lower/12 ms and lower

Life Mechanical life: 20 million and more times, electrical life: rated switching current: 100 thousand and more times

Voltage status display LED On when output voltage is normal

Specification of cable 0.75~2mm²

Available clamped terminal RAV1.25-3.5, RAV2-3.5

Dimension (W x H x D mm) 55 x 95 x 90

Weight 382g

www.AutoDCSTech.com