Honeywell 900H01-0202 Manual

Brand	Honeywell
Product Series	Honeywell
Product Type	-

Description

Honeywell Relay Output Module, 8 Channel (900H01-0202)
The Relay Output Module provides eight individually isolated, electromechanical relay outputs. Four of the outputs are FormC, and the other four are Form-A. Output is not fused in the Relay module. Install a fuse for each output at the field device that is appropriate for the load and the wire used.
There is a green LED state indicator for each channel on the module to indicate when a digital output is ON.
A green blinking status LED on the module indicates when the module is being scanned. A red status LED when module or channel diagnostics exist.
Item Specification
Output channel 4 form A, 4 form C
Output Device Electromechanical relay
Voltage 120/240VAC, 30 VDC
Current Rating 4A @ 240VAC or 30VDC resistive load
0.5 A @ 240VAC or 30VDC incandescent lamp load
www.AutoDCSTech.com
Galvanic Isolation Relay Output Contact to Relay Output Contact
Relay Output Contact to Logic
Max. Leakage Current 1 mA@ 350 VDC
De-rating Max. outputs at max. load – none
Max. modules per rack - none
OFF to ON response time1 11 ms max
ON to OFF response time1 8 ms max
Expected life (min. operations) Mechanical at 180 cpm: 5 x 10E7
Electrical: 10E5
Fail Safe State configuration Yes
 Hold Last State
 Failsafe State
Note:
1. Excluding controllers scan time and excluding transmission time from module to backplane.