

Siemens 3RT6015-1BB42 Manual

Brand	Siemens
Product Series	Siemens
Product Type	designation 3RT2

Description

3RT2015-1BB42

power contactor, AC-3e/AC-3, 7 A, 3 kW / 400 V, 3-pole, 24 V DC, auxiliary

contacts: 1 NC, screw terminal, size: S00

product brand name SIRIUS

product designation Power contactor

product type designation 3RT2

General technical data

size of contactor S00

product extension

- function module for communication No

- auxiliary switch Yes

power loss [W] for rated value of the current

- at AC in hot operating state 0.6 W

- at AC in hot operating state per pole 0.2 W

- without load current share typical 4 W

type of calculation of power loss depending on pole quadratic

insulation voltage

- of main circuit with degree of pollution 3 rated value 690 V

- of auxiliary circuit with degree of pollution 3 rated value 690 V

surge voltage resistance

- of main circuit rated value 6 kV

- of auxiliary circuit rated value 6 kV

maximum permissible voltage for protective separation between

coil and main contacts according to EN 60947-1

400 V

shock resistance at rectangular impulse

- at DC 6,7g / 5 ms, 4,2g / 10 ms

shock resistance with sine pulse

- at DC 10,5g / 5 ms, 6,6g / 10 ms

mechanical service life (operating cycles)

- of contactor typical 30 000 000

- of the contactor with added electronically optimized

auxiliary switch block typical

5 000 000

- of the contactor with added auxiliary switch block typical 10 000 000

reference code according to IEC 81346-2 Q

Substance Prohibitance (Date) 10/01/2009

Weight 0.292 kg

Ambient conditions

installation altitude at height above sea level maximum 2 000 m

ambient temperature

- during operation -25 ... +60 °C
- during storage -55 ... +80 °C

relative humidity minimum 10 %

relative humidity at 55 °C according to IEC 60068-2-30

maximum

95 %

Environmental footprint

Environmental Product Declaration (EPD) Yes

Global Warming Potential [CO₂ eq] total 153 kg

Global Warming Potential [CO₂ eq] during manufacturing 1.42 kg

Global Warming Potential [CO₂ eq] during operation 152 kg

Global Warming Potential [CO₂ eq] after end of life -0.305 kg

Main circuit

number of poles for main current circuit 3

number of NO contacts for main contacts 3

operating voltage

- at AC-3 rated value maximum 690 V
- at AC-3e rated value maximum 690 V

operational current

- at AC-1 at 400 V at ambient temperature 40 °C rated

value

18 A

- at AC-1

— up to 690 V at ambient temperature 40 °C rated

value

18 A

— up to 690 V at ambient temperature 60 °C rated

value

16 A

- at AC-3

— at 400 V rated value 7 A

— at 500 V rated value 6 A

— at 690 V rated value 4.9 A

- at AC-3e

— at 400 V rated value 7 A

— at 500 V rated value 6 A

— at 690 V rated value 4.9 A

- at AC-4 at 400 V rated value 6.5 A

- at AC-5a up to 690 V rated value 15.8 A

- at AC-5b up to 400 V rated value 5.8 A

- at AC-6a

— up to 230 V for current peak value n=20 rated value 4 A

— up to 400 V for current peak value n=20 rated value 4 A

— up to 500 V for current peak value n=20 rated value 3.8 A

— up to 690 V for current peak value n=20 rated value 3.6 A

www.AutoDCSTech.com

- at AC-6a

- up to 230 V for current peak value $n=30$ rated value 2.7 A
- up to 400 V for current peak value $n=30$ rated value 2.7 A
- up to 500 V for current peak value $n=30$ rated value 2.5 A
- up to 690 V for current peak value $n=30$ rated value 2.4 A

minimum cross-section in main circuit at maximum AC-1 rated value

2.5 mm²

operational current for approx. 200000 operating cycles at AC-4

- at 400 V rated value 2.6 A
- at 690 V rated value 1.8 A

operational current

- at 1 current path at DC-1

- at 24 V rated value 15 A
- at 60 V rated value 15 A
- at 110 V rated value 1.5 A
- at 220 V rated value 0.6 A
- at 440 V rated value 0.42 A
- at 600 V rated value 0.42 A

- with 2 current paths in series at DC-1

- at 24 V rated value 15 A
- at 60 V rated value 15 A
- at 110 V rated value 8.4 A
- at 220 V rated value 1.2 A
- at 440 V rated value 0.6 A
- at 600 V rated value 0.5 A

www.AutoDCSTech.com

- with 3 current paths in series at DC-1

- at 24 V rated value 15 A
- at 60 V rated value 15 A
- at 110 V rated value 15 A
- at 220 V rated value 15 A
- at 440 V rated value 0.9 A
- at 600 V rated value 0.7 A

- at 1 current path at DC-3 at DC-5

- at 24 V rated value 15 A
- at 60 V rated value 0.35 A

- with 2 current paths in series at DC-3 at DC-5

- at 24 V rated value 15 A
- at 60 V rated value 3.5 A
- at 110 V rated value 0.25 A

- with 3 current paths in series at DC-3 at DC-5

- at 24 V rated value 15 A
- at 60 V rated value 15 A
- at 110 V rated value 15 A
- at 220 V rated value 1.2 A
- at 440 V rated value 0.14 A
- at 600 V rated value 0.14 A

operating power

- at AC-3

- at 230 V rated value 1.5 kW
- at 400 V rated value 3 kW
- at 500 V rated value 3 kW
- at 690 V rated value 4 kW

- at AC-3e

- at 230 V rated value 1.5 kW
- at 400 V rated value 3 kW
- at 500 V rated value 3 kW
- at 690 V rated value 4 kW

operating power for approx. 200000 operating cycles at AC4

- at 400 V rated value 1.15 kW
- at 690 V rated value 1.15 kW

operating apparent power at AC-6a

- up to 230 V for current peak value n=20 rated value 1.5 kVA
- up to 400 V for current peak value n=20 rated value 2.7 kVA
- up to 500 V for current peak value n=20 rated value 3.3 kVA
- up to 690 V for current peak value n=20 rated value 4.3 kVA

operating apparent power at AC-6a

- up to 230 V for current peak value n=30 rated value 1 kVA
- up to 400 V for current peak value n=30 rated value 1.8 kVA
- up to 500 V for current peak value n=30 rated value 2.2 kVA
- up to 690 V for current peak value n=30 rated value 2.9 kVA

short-time withstand current in cold operating state up to

40 °C

- limited to 1 s switching at zero current maximum 120 A; Use minimum cross-section acc. to AC-1 rated value
- limited to 5 s switching at zero current maximum 86 A; Use minimum cross-section acc. to AC-1 rated value
- limited to 10 s switching at zero current maximum 67 A; Use minimum cross-section acc. to AC-1 rated value
- limited to 30 s switching at zero current maximum 52 A; Use minimum cross-section acc. to AC-1 rated value
- limited to 60 s switching at zero current maximum 43 A; Use minimum cross-section acc. to AC-1 rated value

no-load switching frequency

- at DC 10 000 1/h

operating frequency

- at AC-1 maximum 1 000 1/h
- at AC-2 maximum 750 1/h
- at AC-3 maximum 750 1/h
- at AC-3e maximum 750 1/h
- at AC-4 maximum 250 1/h

Control circuit/ Control

type of voltage of the control supply voltage DC

control supply voltage at DC rated value 24 V

operating range factor control supply voltage rated value of

magnet coil at DC

- initial value 0.8
- full-scale value 1.1

closing power of magnet coil at DC 4 W

holding power of magnet coil at DC 4 W

closing delay

- at DC 30 ... 100 ms

opening delay

- at DC 7 ... 13 ms

arcing time 10 ... 15 ms

control version of the switch operating mechanism Standard A1 - A2

Auxiliary circuit

number of NC contacts for auxiliary contacts instantaneous

contact

1

operational current at AC-12 maximum 10 A

operational current at AC-15

- at 230 V rated value 10 A
- at 400 V rated value 3 A
- at 500 V rated value 2 A
- at 690 V rated value 1 A

operational current at DC-12

- at 24 V rated value 10 A
- at 48 V rated value 6 A
- at 60 V rated value 6 A
- at 110 V rated value 3 A
- at 125 V rated value 2 A
- at 220 V rated value 1 A
- at 600 V rated value 0.15 A

operational current at DC-13

- at 24 V rated value 10 A
- at 48 V rated value 2 A
- at 60 V rated value 2 A
- at 110 V rated value 1 A
- at 125 V rated value 0.9 A
- at 220 V rated value 0.3 A
- at 600 V rated value 0.1 A

contact reliability of auxiliary contacts 1 faulty switching per 100 million (17 V, 1 mA)

UL/CSA ratings

full-load current (FLA) for 3-phase AC motor

- at 480 V rated value 4.8 A
- at 600 V rated value 6.1 A

yielded mechanical performance [hp]

- for single-phase AC motor
 - at 110/120 V rated value 0.25 hp
 - at 230 V rated value 0.75 hp
- for 3-phase AC motor
 - at 200/208 V rated value 1.5 hp
 - at 220/230 V rated value 2 hp
 - at 460/480 V rated value 3 hp
 - at 575/600 V rated value 5 hp

contact rating of auxiliary contacts according to UL A600 / Q600

Short-circuit protection

design of the fuse link

- for short-circuit protection of the main circuit
 - with type of coordination 1 required gG: 35A (690V, 100kA), aM: 20A (690V, 100kA), BS88: 35A (415V, 80kA)
 - with type of assignment 2 required gG: 20A (690V, 100kA), aM: 16A (690V, 100kA), BS88: 20A (415V, 80kA)
- for short-circuit protection of the auxiliary switch required gG: 10 A (500 V, 1 kA)

www.AutoDCSTech.com

Installation/ mounting/ dimensions

mounting position $\pm 180^\circ$ rotation possible on vertical mounting surface; can be tilted forward and backward by $\pm 22.5^\circ$ on vertical mounting surface

fastening method screw and snap-on mounting onto 35 mm DIN rail according to DIN EN 60715

height 58 mm

width 45 mm

depth 73 mm

required spacing

- with side-by-side mounting

— forwards 10 mm

— upwards 10 mm

— downwards 10 mm

— at the side 0 mm

- for grounded parts

— forwards 10 mm

— upwards 10 mm

— at the side 6 mm

— downwards 10 mm

- for live parts

— forwards 10 mm

— upwards 10 mm

— downwards 10 mm

— at the side 6 mm

Connections/ Terminals

www.AutoDCSTech.com

type of electrical connection

- for main current circuit screw-type terminals
- for auxiliary and control circuit screw-type terminals
- at contactor for auxiliary contacts Screw-type terminals
- of magnet coil Screw-type terminals

type of connectable conductor cross-sections

- for main contacts

— solid 2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²), 2x 4 mm²

— solid or stranded 2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²), 2x 4 mm²

— finely stranded with core end processing 2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²)

- for AWG cables for main contacts 2x (20 ... 16), 2x (18 ... 14), 2x 12

connectable conductor cross-section for main contacts

- solid 0.5 ... 4 mm²

- stranded 0.5 ... 4 mm²

- finely stranded with core end processing 0.5 ... 2.5 mm²

connectable conductor cross-section for auxiliary contacts

- solid or stranded 0.5 ... 4 mm²

- finely stranded with core end processing 0.5 ... 2.5 mm²

type of connectable conductor cross-sections

- for auxiliary contacts

— solid or stranded 2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²), 2x 4 mm²

— finely stranded with core end processing 2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²)

- for AWG cables for auxiliary contacts 2x (20 ... 16), 2x (18 ... 14), 2x 12

AWG number as coded connectable conductor cross

section

- for main contacts 20 ... 12

- for auxiliary contacts 20 ... 12

Safety related data

product function

- mirror contact according to IEC 60947-4-1 Yes
- positively driven operation according to IEC 60947-5-1 No
- suitable for safety function Yes

suitability for use safety-related switching OFF Yes

service life maximum 20 a

test wear-related service life necessary Yes

proportion of dangerous failures

- with low demand rate according to SN 31920 40 %

- with high demand rate according to SN 31920 73 %

B10 value with high demand rate according to SN 31920 1 000 000

failure rate [FIT] with low demand rate according to SN 31920

100 FIT

ISO 13849

device type according to ISO 13849-1 3

overdimensioning according to ISO 13849-2 necessary Yes

IEC 61508

safety device type according to IEC 61508-2 Type A

Electrical Safety

protection class IP on the front according to IEC 60529 IP20

touch protection on the front according to IEC 60529 finger safe, for vertical contact from the front

www.AutoDCSTech.com

Technical Specifications

size of contactor S00

product extension

- function module for communication No
- auxiliary switch Yes

power loss [W] for rated value of the current

- at AC in hot operating state 0.6 W
- at AC in hot operating state per pole 0.2 W
- without load current share typical 4 W

type of calculation of power loss depending on pole quadratic

insulation voltage

- of main circuit with degree of pollution 3 rated value 690 V
- of auxiliary circuit with degree of pollution 3 rated value 690 V

surge voltage resistance

- of main circuit rated value 6 kV
- of auxiliary circuit rated value 6 kV

maximum permissible voltage for protective separation between coil and main contacts according to EN 60947-1

400 V

shock resistance at rectangular impulse

- at DC 6,7g / 5 ms, 4,2g / 10 ms

shock resistance with sine pulse

- at DC 10,5g / 5 ms, 6,6g / 10 ms
- mechanical service life (operating cycles)
- of contactor typical 30 000 000
 - of the contactor with added electronically optimized auxiliary switch block typi

www.AutoDCSTech.com