

Siemens 3RW4458-6BC44 Manual

Brand	Siemens
Product Series	Siemens
Product Type	is >>3RW5556-

Description

3RW4458-6BC44

SIRIUS soft starter Values at 400 V, 40 °C standard: 970 A,
560 kW Inside-delta: 1680 A, 1000 kW 200-460 V AC, 230 V
AC Screw terminals !!! Phased-out product !!! Successor is
SIRIUS 3RW5, Preferred successor type is >>3RW5556-
6HA14<<

General technical data

product brand name SIRIUS

product feature

- integrated bypass contact system Yes
- thyristors Yes

product function

- intrinsic device protection Yes
- motor overload protection Yes
- evaluation of thermistor motor protection Yes
- external reset Yes
- adjustable current limitation Yes
- inside-delta circuit Yes

product component motor brake output Yes

insulation voltage rated value V 690

degree of pollution 3, acc. to IEC 60947-4-2

reference code acc. to DIN EN 61346-2 Q

reference code acc. to DIN 40719 extended according
to IEC 204-2 acc. to IEC 750

G

Power Electronics

product designation Soft starter

operational current

- at 40 °C rated value A 970
- at 50 °C rated value A 850
- at 60 °C rated value A 760

operational current for 3-phase motors at inside-delta
circuit

- at 40 °C rated value A 1 680
- at 50 °C rated value A 1 472
- at 60 °C rated value A 1 316

yielded mechanical performance for 3-phase motors

www.AutoDCSTech.com

- at 230 V
 - at standard circuit at 40 °C rated value W 315 000
 - at inside-delta circuit at 40 °C rated value W 560 000
 - at 400 V
 - at standard circuit at 40 °C rated value W 560 000
 - at inside-delta circuit at 40 °C rated value W 1 000 000
- yielded mechanical performance [hp] for 3-phase AC
motor at 200/208 V at standard circuit at 50 °C rated
value
hp 300

operating frequency rated value Hz 50 ... 60
relative negative tolerance of the operating frequency % -10
relative positive tolerance of the operating frequency % 10
operating voltage at standard circuit rated value V 200 ... 460
relative negative tolerance of the operating voltage at
standard circuit
% -15
relative positive tolerance of the operating voltage at
standard circuit
% 10
operating voltage at inside-delta circuit rated value V 200 ... 460
relative negative tolerance of the operating voltage at
inside-delta circuit
% -15
relative positive tolerance of the operating voltage at
inside-delta circuit
% 10
minimum load [%] % 8
adjustable motor current for motor overload
protection minimum rated value
A 194
continuous operating current [% of I_e] at 40 °C % 115
power loss [W] at operational current at 40 °C during
operation typical
W 270

Control circuit/ Control

type of voltage of the control supply voltage AC

control supply voltage frequency 1 rated value Hz 50

control supply voltage frequency 2 rated value Hz 60

relative negative tolerance of the control supply
voltage frequency

% -10

relative positive tolerance of the control supply
voltage frequency

% 10

control supply voltage 1 at AC

- at 50 Hz rated value V 230

- at 60 Hz rated value V 230

relative negative tolerance of the control supply
voltage at AC at 50 Hz

www.AutoDCSTech.com

% -15

relative positive tolerance of the control supply

voltage at AC at 50 Hz

% 10

relative negative tolerance of the control supply

voltage at AC at 60 Hz

% -15

relative positive tolerance of the control supply

voltage at AC at 60 Hz

% 10

display version for fault signal Display

Mechanical data

width mm 510

height mm 640

depth mm 290

fastening method screw fixing

mounting position with vertical mounting surface +/-90° rotatable, with

vertical mounting surface +/- 22.5° tiltable to the front and

back

required spacing with side-by-side mounting

- upwards mm 100
- at the side mm 5
- downwards mm 75

wire length maximum m 500

number of poles for main current circuit 3

Connections/ Terminals

type of electrical connection

- for main current circuit busbar connection
- for auxiliary and control circuit screw-type terminals

number of NC contacts for auxiliary contacts 0

number of NO contacts for auxiliary contacts 3

number of CO contacts for auxiliary contacts 1

type of connectable conductor cross-sections for DIN

cable lug for main contacts

- finely stranded 50 ... 240 mm²
- stranded 70 ... 240 mm²

type of connectable conductor cross-sections for

auxiliary contacts

- solid 2x (0.5 ... 2.5 mm²)
- finely stranded with core end processing 2x (0.5 ... 1.5 mm²)

type of connectable conductor cross-sections at AWG

cables

- for main contacts 2/0 ... 500 kcmil
- for auxiliary contacts 2x (20 ... 14)
- for auxiliary contacts finely stranded with core end

processing

2x (20 ... 16)

Ambient conditions

installation altitude at height above sea level m 5 000

environmental category

www.AutoDCSTech.com

- during transport acc. to IEC 60721 2K2, 2C1, 2S1, 2M2 (max. fall height 0.3 m)
- during storage acc. to IEC 60721 1K6 (only occasional condensation), 1C2 (no salt mist), 1S2 (sand must not get inside the devices), 1M4
- during operation acc. to IEC 60721 3K6 (no formation of ice, no condensation), 3C3 (no salt mist), 3S2 (sand must not get into the devices), 3M6

ambient temperature

- during operation °C 60
- during storage °C -25 ... +80

derating temperature °C 40

protection class IP IP00

Technical Specifications

product brand name SIRIUS

product feature

- integrated bypass contact system Yes
- thyristors Yes

product function

- intrinsic device protection Yes
- motor overload protection Yes
- evaluation of thermistor motor protection Yes
- external reset Yes
- adjustable current limitation Yes
- inside-delta circuit Yes

product component motor brake output Yes

insulation voltage rated value V 690

degree of pollution 3, acc. to IEC 60947-4-2

reference code acc. to DIN EN 61346-2 Q

reference code acc. to DIN 40719 extended according

to IEC 204-2 acc. to IEC 750

G

Power Electronics

product designation Soft starter

operational current

- at 40 °C rated value A 970
- at 50 °C rated value A 850
- at 60 °C rated value A 760

operational current for 3-phase motors at inside-delta

circuit

- at 40 °C rated value A 1 680
- at 50 °C rated value A 1 472
- at 60 °C rated value A 1 316

yielded mechanical performance for 3-phase motors

- at 230 V
- at standard circuit at 40 °C rated value W 315 000
- at inside-d

www.AutoDCSTech.com