

Siemens 6ES7136-6RA00-0BF0 Manual

Brand	Siemens
Product Series	Siemens
Product Type	designation F-RQ 1x24VDC/24 ... 230VAC/5A

Description

igital output module
F-RQ 1x24VDC/24...230VAC/5A
(6ES7136-6RA00-0BF0)

SIMATIC
ET 200SP
Digital output module
F-RQ 1x24VDC/24...230VAC/5A

Technical specifications

Technical specifications of F-RQ 1x24VDC/24...230VAC/5A

6ES7136-6RA00-0BF0

Product type designation F-RQ 1x24VDC/24...230VAC/5A

General information

Hardware product version 01

Firmware version V1.0.0

Product function

I&M data Yes; I&M0 to I&M3

Engineering with

STEP 7 TIA Portal configurable/integrated as of
version

V13

STEP 7 configurable/integrated as of version V5.5 SP4 and higher

Installation type/mounting

Rail mounting possible Yes; standard mounting rail

Supply voltage

Type of supply voltage 24 VDC

Rated value (DC) 24 V; coil voltage

Low limit of permitted range (DC) 20.4 V

High limit of permitted range (DC) 28.8 V

Power

Power consumption from the backplane bus 100 mW

Power loss

Power loss, typ. 1 W

Address range

Address space per module

Input 1 byte

Digital outputs

Number of outputs 1

www.AutoDCSTech.com

Voltage induced on current interruption limited to No

Control of a digital input Yes

Switching capacity of outputs

With resistive load, max. 5 A

With lamp load, max. 25 W

Technical Specifications

6ES7136-6RA00-0BF0

Product type designation F-RQ 1x24VDC/24 ... 230VAC/5A

General information

Hardware product version 01

Firmware version V1.0.0

Product function

I&M data Yes; I&M0 to I&M3

Engineering with

STEP 7 TIA Portal configurable/integrated as of

version

V13

STEP 7 configurable/integrated as of version V5.5 SP4 and higher

Installation type/mounting

Rail mounting possible Yes; standard mounting rail

Supply voltage

Type of supply voltage 24 VDC

Rated value (DC) 24 V; coil voltage

Low limit of permitted range (DC) 20.4 V

High limit of permitted range (DC) 28.8 V

Power

Power consumption from the backplane bus 100 mW

Power loss

Power loss, typ. 1 W

Address range

Address space per module

Input 1 byte

Digital outputs

Number of outputs 1

Voltage induced on current interruption limited to No

Control of a digital input Yes

Switching capacity of outputs

With resistive load, max. 5 A

With lamp load, max. 25 W

www.AutoDCSTech.com