

Siemens 6ES7223-1BL32-0XB0 Manual

Brand	Siemens
Product Series	Siemens
Product Type	designation SM 1223, DI 16x24 V DC, DQ 16x24 V DC

Description

6ES7223-1BL32-0XB0

SIMATIC S7-1200, Digital I/O SM 1223, 16 DI/16 DO, 16 DI 24 V DC, Sink/Source, 16 DO, transistor 0.5 A

General information

Product type designation SM 1223, DI 16x24 V DC, DQ 16x24 V DC

Supply voltage

Rated value (DC) 24 V

permissible range, lower limit (DC) 20.4 V

permissible range, upper limit (DC) 28.8 V

Input current

from backplane bus 5 V DC, max. 185 mA

Digital inputs

- from load voltage L+ (without load), max. 4 mA; per channel

output voltage / header

supply voltage of the transmitters / header

- present Yes

Power loss

Power loss, typ. 4.5 W

Digital inputs

Number of digital inputs 16

- in groups of 2

Input characteristic curve in accordance with IEC 61131, type 1 Yes

Number of simultaneously controllable inputs

all mounting positions

— up to 40 °C, max. 16

horizontal installation

— up to 40 °C, max. 16

— up to 50 °C, max. 16

vertical installation

— up to 40 °C, max. 16

Input voltage

- Type of input voltage DC
- Rated value (DC) 24 V
- for signal "0" 5 V DC at 1 mA
- for signal "1" 15 V DC at 2.5 mA

Input current

- for signal "0", max. (permissible quiescent current) 1 mA
- for signal "1", min. 2.5 mA

www.AutoDCSTech.com

- for signal "1", typ. 4 mA

Input delay (for rated value of input voltage)

for standard inputs

— parameterizable Yes; 0.2 ms, 0.4 ms, 0.8 ms, 1.6 ms, 3.2 ms, 6.4 ms and 12.8 ms, selectable in groups of four

for interrupt inputs

— parameterizable Yes

Cable length

- shielded, max. 500 m
- unshielded, max. 300 m

Digital outputs

Number of digital outputs 16

- in groups of 1

Short-circuit protection No; to be provided externally

Limitation of inductive shutdown voltage to L+ (-48 V)

Switching capacity of the outputs

- with resistive load, max. 0.5 A
- on lamp load, max. 5 W

Output voltage

- Rated value (DC) 24 V
- for signal "0", max. 0.1 V; with 10 kOhm load
- for signal "1", min. 20 V DC

Output current

- for signal "1" rated value 0.5 A
- for signal "1" permissible range, max. 0.5 A
- for signal "0" residual current, max. 10 μ A

Output delay with resistive load

- "0" to "1", max. 50 μ s
- "1" to "0", max. 200 μ s

Total current of the outputs (per group)

horizontal installation

— up to 50 °C, max. 8 A; Current per mass

Relay outputs

Switching capacity of contacts

- with inductive load, max. 0.5 A
- on lamp load, max. 5 W
- with resistive load, max. 0.5 A

Cable length

- shielded, max. 500 m
- unshielded, max. 150 m

Interrupts/diagnostics/status information

Alarms

- Diagnostic alarm Yes

Diagnostics indication LED

- for status of the inputs Yes
- for status of the outputs Yes

Potential separation

Potential separation digital inputs

- between the channels, in groups of 2

Potential separation digital outputs

www.AutoDCSTech.com

- between the channels, in groups of 1
- between the channels and backplane bus 500 V AC

Degree and class of protection

IP degree of protection IP20

Standards, approvals, certificates

CE mark Yes

CSA approval Yes

UL approval Yes

cULus Yes

FM approval Yes

RCM (formerly C-TICK) Yes

KC approval Yes

Marine approval Yes

Ambient conditions

Free fall

- Fall height, max. 0.3 m; five times, in product package

Ambient temperature during operation

- min. -20 °C
- max. 60 °C
- horizontal installation, min. -20 °C
- horizontal installation, max. 60 °C
- vertical installation, min. -20 °C
- vertical installation, max. 50 °C
- permissible temperature change 3 °C to 55 °C, 3 °C/minute

Ambient temperature during storage/transportation

- min. -40 °C
- max. 70 °C

Air pressure acc. to IEC 60068-2-13

- Storage/transport, min. 660 hPa
- Storage/transport, max. 1 080 hPa

Relative humidity

- Operation at 25 °C without condensation, max. 95 %

connection method

required front connector Yes

Mechanics/material

Enclosure material (front)

- Plastic Yes

Dimensions

Width 70 mm

Height 100 mm

Depth 75 mm

Weights

Weight, approx. 310 g

www.AutoDCSTech.com