

# Siemens 6ES7340-1AH01-0AE0 Manual

|                |                |
|----------------|----------------|
| Brand          | Siemens        |
| Product Series | Siemens        |
| Product Type   | RS 232C (V.24) |

## Description

6ES7340-1AH01-0AE0

SIMATIC S7-300, CP 340 COMMUNICATION PROCESSOR WITH  
RS232C INTERFACE (V.24) INCL. CONFIG. PACKAGE ON CD

Input current

from backplane bus 5 V DC, max. 165 mA

Power loss

Power loss, max. 0.85 W

Interfaces

Interfaces/bus type RS 232C (V.24)

Number of interfaces 1; Isolated

Transmission rate, min. 2.4 kbit/s

Transmission rate, max. 19.2 kbit/s

Point-to-point connection

[www.AutoDCSTech.com](http://www.AutoDCSTech.com)

- Cable length, max. 15 m
- supported printers HP-Deskjet, HP-Laserjet, IBM-Proprinter, user-defined

Telegram length, max.

— 3964 (R) 1 024 byte

— ASCII 1 024 byte

Transmission speed, RS 232

— with 3964 (R) protocol, max. 19.2 kbit/s

— with ASCII protocol, max. 9.6 kbit/s

— with printer driver, max. 9.6 kbit/s

Software

Block

- FB length in RAM, max. 2 700 byte; Data communication, sending and receiving

Dimensions

Width 40 mm

Height 125 mm

Depth 120 mm

Weights

Weight, approx. 300 g