

Siemens 6ES7392-1AJ00-0AA0 Manual

Brand	Siemens
Product Series	Siemens
Product Type	designation Front connector

Description

6ES7392-1AJ00-0AA0

MFN: 6ES73921AJ000AA0

Front Connector, 20pin,Screw Cont.

SIMATIC S7-300, Front connector for signal modules with screw contacts, 20-pole

Packaging dimensions (L x W x H)

5.63 x 1.65 x 1.14 inch

Net weight

0.152 lb

General information

www.AutoDCSTech.com

Product type designation Front connector

Ambient conditions

Ambient temperature during operation

- min. 0 °C
- max. 60 °C

Ambient temperature during storage/transportation

- min. -40 °C
- max. 70 °C

Accessories

belongs to product S7-300

connection method

Connection I/O signals

- Connection method Screw terminals
- Number of lines per connection 1; or combination of 2 conductors of up to 1.5 mm² (total) in a shared ferrule

Conductor cross-section in mm²

— Connectable cable cross-sections for massive cables, min.

0.25 mm²

— Connectable cable cross-sections for massive cables, min.

1.5 mm²

— Connectable cable cross-sections for flexible cables without end sleeve, min.

0.25 mm²

— Connectable cable cross-sections for flexible cables without end sleeve, max.

1.5 mm²

— Connectable cable cross-sections for flexible cables
with end sleeve, min.

0.25 mm²

— Connectable cable cross-sections for flexible cables
with end sleeve, max.

1.5 mm²

Conductor cross-section acc. to AWG

— Connectable cable cross-sections for massive
cables, min.

24

— Connectable cable cross-sections for massive
cables, min.

16

— Connectable cable cross-sections for flexible cables
without end sleeve, min.

24

— Connectable cable cross-sections for flexible cables
without end sleeve, max.

16

— Connectable cable cross-sections for flexible cables
with end sleeve, min.

24

— Connectable cable cross-sections for flexible cables
with end sleeve, max.

16

Wire end processing

— Stripped length of cables, min. 6 mm

— Stripped length of cables, max. 6 mm

— End sleeve acc. to DIN 46228 without plastic sleeve Design A, 5 mm to 7 mm long

— End sleeve acc. to DIN 46228 with plastic sleeve Design E, up to 6 mm long

Mounting

— Tool Screwdriver, conical design, 3 mm to 3.5 mm

— Tightening torque, min. 0.4 N·m

— Tightening torque, max. 0.7 N·m

Dimensions

Width 23 mm

Height 131 mm

Depth 36 mm

Weights

Weight, approx. 70 g

www.AutoDCSTech.com