

Siemens 6ES7440-1CS00-0YE0 Manual

Brand	Siemens
Product Series	Siemens
Product Type	-

Description

6ES7440-1CS00-0YE0

SIMATIC S7-400, CP 440-1 COMMUNICATIONS MODULE FOR
POINT TO POINT CONNECTIONS 1 CHANNEL INCL. CONFIG.
PACKAGE ON CD

Supply voltage

Rated value (DC)

- 5 V DC Yes
- 24 V DC Yes

Input current

from backplane bus 5 V DC, max. 360 mA

Power loss

Power loss, typ. 1.7 W

Memory

Memory requirements per interface in memory card
of S7-CPU

1 to 5 Kbytes for parameters

Interfaces

Number of interfaces 1

Interface (physical) RS 422/485 (X.27) Yes

RS 422/RS 485, cable length shielded, max. 1 200 m

Point-to-point

Integrated protocol driver

- 3964 (R) Yes
- ASCII Yes

Transmission rate, RS 422/485

- with 3964 (R) protocol, max. 115.2 kbit/s
- with ASCII protocol, max. 115.2 kbit/s

Configuration

Configuration software

- STEP 7 Yes; own parameter assignment forms

Dimensions

Width 25 mm

Height 290 mm

Depth 210 mm

Weights

Weight, approx. 600 g

www.AutoDCSTech.com