

Bently Nevada 9200-06-02-01-00 Manual

Brand	Bently Nevada
Product Series	9200
Product Type	Two-Wire Velocity Seismoprobe Transducer

Description

Part Number: 9200-06-02-01-00

Model: Two-Wire Velocity Seismoprobe Transducer

Manufacturer: Bently Nevada

Condition: New & Original in Factory Packing

Factory Warranty: 12 Months

Ordering Information

Model 9200 Two-wire Transducer

Transducer Mounting Angle/Minimum Operating Frequency Option 06= 0 ±100, 10 Hz (600 cpm)

Connector Option : 02 =Side Mount (no cable)

Mounting Base Option : 01= Circular; 1/4-20 UNC stud

Agency Approval Option 00= No agency approval required

Sensitivity

20 mV/mm/s (500 mV/in/s),

±5% when properly terminated

and oriented at the angle of

calibration.

Calibration

Load

10 k Ω Terminal "A" to "B" Output

taken across pins "A" and "B"

Sensitivity

Temperature

Coefficient

0.2%/°C

Dynamic

operating

range

2.54 mm (0.100 in) peak to

peak maximum displacement.

Velocity

Range

25 mm/s (1 in/s) (at +22 °C of

casing vibration at 100 Hz with

a 10 k Ω load.

Coil

www.AutoDCSTech.com

Resistance 1.25 k Ω $\pm$ 5%
Locked Coil
Inductance 125 mH, typical

Operating
and Storage

Temperature:

9200: -29°C to +121°C

(-20°F to +250°F).

74712: -29°C to +204°C

(-20°F to +400°F).

Environment

Dust and moisture resistant.

Relative

Humidity

To 95%, noncondensing.

100%, non-submerged, when
ordered with integral cable.

Case and

Adapter

Material

Anodized aluminum A204

Gasket

Material

9200: Neoprene

www.AutoDCSTech.com

Height

102 mm (4 in) typical

(depending on connector
option).

Diameter 41 mm (1.6 in) typical.

Weight

9200

= 300 grams (10.5
ounces) typical.