

Yokogawa AFV30D-A41252 Manual

Brand	Yokogawa
Product Series	Yokogawa
Product Type	Field Control Unit

Description

AFV30D-A41252 | Yokogawa | Field Control Unit

Manufacturer : Yokogawa

Product No. : AFV30D-A41252

Product Type : Field Control Unit

AFV30D - Duplexed Field Control Unit (for Vnet/IP and FIO, 19-inch Rack Mountable)

A - Standard type(for CP471)(*1)

4 - Dual-redundant Vnet/IP, dual-redundant power supply

1 - Always 1

2 - 220-240 V AC power supply(*4)

5 - Basic type with no explosion protection

2 - Always 2(R6.01 or later)

Approx. 8.0 kg

Power Consumption

100-120 V AC: 200 VA

220-240 V AC: 230 VA

24 V DC: 5.5 A

I Weight

Approx. 7.0 kg (AFV30S)

Approx. 8.0 kg (AFV30D)

I Mounting

19-inch Rack Mounting: Rack mount (M5x8 screws), Insulation bush (accessory)

I Connection

Power Supply: M4 screw terminal connection

Grounding: M4 screw terminal connection

READY Contact Output: M4 screw terminal connection

Network: Connect UTP cable (CAT5e or better) to Layer 2 switch