

Yokogawa SDV144-S63 Manual

Brand	Yokogawa
Product Series	Yokogawa
Product Type	Digital Input Module

Description

Manufacturer : Yokogawa

Product No. : SDV144-S63

Product type : Digital Input Module

Model : SDV144 = Digital Input Module (16-channel, 24 V DC, module isolation)

Suffix Codes : S = Standard type

Suffix Codes : 6 : With signal cable interface adapter and no explosion protection

Suffix Codes : 3 = With ISA Standard G3 and temperature (-20 to 70 °C)

Input signal : No-voltage contact. ON: 1 k Ω maximum. OFF: 100 k Ω minimum.

Input current : 6 mA $\pm$ 20 % (External power supply, 24 V DC at 0 Ω input)

Contact rating : 24 V DC +20 % / -10 % (*4), 10 mA or greater

External power supply : 24 V DC +20 % / -10 %. Current capacity: 200 mA

Instantaneous maximum permissible input voltage : 30.0 V DC

Input response time : 40 ms maximum

Withstand voltage : 2 kV AC between input signal and system for 1 minute, 16-input line collectively connected

Current consumption : 290 mA maximum (5 V DC) 140 mA maximum (24 V DC)

External connection : Pressure clamp terminal, MIL cable, Dedicated signal cable (AKB331)

Weight : 0.41 Kg

Item Specifications

Model SDV144

Number of inputs 16-channel, module isolation

Input signal

No-voltage contact

ON: 1 k Ω maximum

OFF: 100 k Ω minimum

Input current 6 mA $\pm$ 20 %

(External power supply, 24 V DC at 0 Ω input)

Contact rating 24 V DC +20 % / -10 % , 10 mA or greater

External power supply 24 V DC +20 % / -10 %

Current capacity: 200 mA

Instantaneous maximum permissible

input voltage 30.0 V DC

Input response time 40 ms maximum

Withstand voltage 2 kV AC between input signal and system for 1 minute, 16-input line collectively connected

Current consumption 290 mA maximum (5 V DC)

140 mA maximum (24 V DC)

Weight Approx. 0.36 kg (For pressure clamp terminal block or MIL cable)

Approx. 0.41 kg (With signal cable interface adapter)

Website: www.AutoDCSTech.com Email: sales@AutoDCSTech.com

External connection

Pressure clamp terminal

MIL cable

Dedicated signal cable (AKB331)