

A02B-0120-K303

FANUC Corporation · FANUC CNC accessory

FEATURES

Official FANUC identity (per B-64303EN/01 Maintenance/Connection Manual): Recommended cable connector (Hirose, 20-pin). Connector assembly, 15-pin female with cover, for FANUC CNC wiring.

Hardware

Connector kit:

Hirose FI40B-2015S (connector) + FI-20-CV (case), soldering type, for JA3 on operators panel depth 80 mm min. (family-level reference; cross-generation manual not confirmed for this specific order code (per GFZ-63523EN/03 §9.13.3.10, p.380)

Communication

Electrical

Supply voltage:

Not applicable (passive component; cable/connector/fuse/memory card; powered by host system)

Power consumption:

Not applicable (passive component; no independent power consumption)

Environmental

Operating temperature:

Not applicable (passive component; rating follows host CNC)

Storage temperature:

Not applicable (passive component; rating follows host CNC)

Relative humidity:

75%RH or less normal; up to 95%RH for short periods (≤1 month), no condensation (official per B-63945EN/02 Maintenance Manual §5.10 Environmental Conditions, p.329/printed 356)

Physical

Dimensions (H×W×D):

Not applicable (passive connector kit; no manufacturer-published outline dimensions)

Weight:

~0.03 kg (supplier-reported; family-level reference; not confirmed for this specific order code; per DO Supply K321 connector kit)

Lifecycle

Legacy (spare-part connector for FANUC Series 16/18 CNC; Series 16/18 is a legacy control generation) (Last verified:

2026-09)

www.AutoDCSTech.com