

A02B-0120-K324

FANUC Corporation · FANUC CNC accessory

FEATURES

Official FANUC identity (per B-64303EN/01 Maintenance/Connection Manual): Recommended cable-side connector (24V power, AMP). CX2A/CX2B power connector kit with 3-pin female contacts for FANUC Series 16/18 CNC.

Hardware

Communication

Electrical

Supply voltage:

Not applicable (passive component; cable/connector/fuse/memory card; powered by host system)

Power consumption:

Not applicable (passive component; no independent power consumption)

Environmental

Operating temperature:

Not applicable (passive component; rating follows host CNC)

Storage temperature:

Not applicable (passive component; rating follows host CNC)

Relative humidity:

75%RH or less normal; up to 95%RH for short periods (≤1 month), no condensation (official per B-63945EN/02 Maintenance Manual §5.10 Environmental Conditions, p.929/printed 356)

Physical

Dimensions (H×W×D):

Not applicable (passive power connector kit; no manufacturer-published outline dimensions)

Weight:

~0.05 kg (supplier-reported; family-level reference; not confirmed for this specific order code; per DO Supply connector kit data)

Lifecycle

Legacy (spare-part power connector kit for FANUC Series 16/18 CNC; Series 16/18 is a legacy control generation) (Last verified:

2026-09)