Mitsubishi □□ □□□ □□□ Series Service Manual

MR-J3-BRKS1-79-25M

1. Description

The MR-J3-BRKS1-79-25M is a specialized H-Flex servo brake cable manufactured by Mitsubishi. It is designed specifically for servo brake connections within the MELSERVO MR-J3 series. The cable's flexible design ensures ease in routing through various installation environments.

2. Specifications

Specification	Value
Manufacturer	**Mitsubishi**
Product	**Line MELSERVO MR-J3**
Part	**Number MR-J3-BRKS1-79-25M**
Application	**Servo brake connection**
Cable	**Structure Flexible design for ease of routing**
Type	**H-Flex Servo Brake Cable**
Compatibility	**Compatible with MELSERVO series**
Operating	**Temperature Range -10°C to 60°C**
Length	**25 meters**
Protection	**Rating Shielded**
Conductors	**Multi-conductor configuration**
Shielding	**Enhanced shielding for durability**
Certification	**NFPA Certified**
Description	
The	**MR-J3-BRKS1-79-25M is designed as a servo brake connection cable within Mitsubishi's MELSERVO MR-J3 series. This cable spans an impressive length of 25 meters, allowing for versatile installation options in various setups. Its construction prioritizes flexibility, making routing and management straightforward and efficient in confined spaces.**

3. Product Information

The MR-J3-BRKS1-79-25M is a specialized H-Flex servo brake cable manufactured by Mitsubishi. It is designed specifically for servo brake connections within the MELSERVO MR-J3 series. The cable's flexible design ensures ease in routing through various installation environments.

Technical specifications for MR-J3-BRKS1-79-25M:

www.AutoDCSTech.com

Manufacturer Mitsubishi

Product Line MELSERVO MR-J3

Part Number MR-J3-BRKS1-79-25M

Application Servo brake connection

Cable Structure Flexible design for ease of routing

Type H-Flex Servo Brake Cable

Compatibility Compatible with MELSERVO series

Operating Temperature Range -10°C to 60°C

Length 25 meters

Protection Rating Shielded

Conductors Multi-conductor configuration

Shielding Enhanced shielding for durability

Certification NFPA Certified

Description

The MR-J3-BRKS1-79-25M is designed as a servo brake connection cable within Mitsubishi's MELSERVO MR-J3 series. This cable spans an impressive length of 25 meters, allowing for versatile installation options in various setups. Its construction prioritizes flexibility, making routing and management straightforward and efficient in confined spaces.

Operating over a temperature range of -10°C to 60°C, the MR-J3-BRKS1-79-25M remains reliable across diverse environmental conditions. The cable incorporates a multi-conductor arrangement, facilitating effective signal transmission while maintaining performance standards.

Weighing 1.36 kilograms, this cable is manageable during installation. The protection rating is enhanced with shielded capabilities, promoting durability and safeguarding against electrical interference. Additionally, the cable is NFPA-certified, confirming adherence to established safety and quality guidelines for electrical components.

In summary, the MR-J3-BRKS1-79-25M H-Flex Servo Brake Cable is a robust solution tailored to meet the demands of the MELSERVO series' servo brake applications.